### SPORTS CAR TOUCHES IN A SETTING OF LUXURY... BUICK WILDCAT



RICHLY-STYLED BUCKET SEATS in a smart



FOAM RUBBER HEAD LINING is a pleasure to look at, a pleasure to touch. Makes a big contribution, too, to Wildcat quietness.



CONVERTIBLE

DEEP CARPETING, color-keyed to Wildcat interior decor, puts extra luxury underfoot. Thick, durable weave means long life and good looks.



RALLYIST'S TACHOMETER set in a handsome con-sole between the seats is a never-ending delight for performance lovers. Standard equipment.



BRIGHT METAL CONSOLE between front seats con-tains Turbine Drive control and indicator as well as tachometer. Standard equipment.



REAR SEAT COURTESY LIGHT is mounted on the back of the console for extra safety and convenience. Lights when door is opened.

# BIG NEMS SEVEONS **WAKES THE** BNICK

Newest additions to a growing family of quality Buicks




THE BUICK WILDCAT Here is a luxurious, new, high-spirited performer in the great Buick tradition. Inside and outside, this Advanced Thrust Wildcat is an enticing invitation to go. You'll love the luxurious vinyl bucket seats, the fingertip convenience of the floor-mounted Turbine Drive control, the surging excitement of the Wildcat 445 engine and particularly the effortless sure-footedness of Advanced Thrust design. Wildcat . . . one of the greatest in a great line of Buicks.



THE BUICK SKYLARK CONVERTIBLE The sky's the limit on fun in this brilliant new Skylark convertible by Buick. Here is everything you expect in a Skylark—flashing 190 lpp. Skylark Aluminum V8 performance, dashing good looks, luxury interiors-plus all the playtime pleasure of a convertible. For your convenience, the sleek top is automatically operated. Bucket seats are standard naturally, in a tantalizing selection of leather-grained washable vinyls.

### DESIGNED FOR PURE PLEASURE ... BUICK SKYLARK CONVERTIBLE






SMART BUCKET SEATS tailored in your choice of rich, leather-grained vanyls. Interiors are color-keyed to exterior color. Five colors to choose from.



PADDED INSTRUMENT PANEL is standard equip-



DELUXE CARPETING, wall to wall, makes stepping into the Skylark convertible a pleasure. Choice of many steatful decorator colors.

AUTOMATIC CONVERTIBLE TOP raises and lowers at the touch of a button. Nests down under smooth-study dual controls at each window, master control at driver's seat.








THE BUICK AND THE BUICK ARK CONVERTIBLE



THE LUXURY OF A BUICK with the zest and flair of a sports car. That's the interior of the brilliant new Buick Wildcat.







### THINGS YOU SHOULD KNOW ABOUT

## THE BUICK



STANDARD EQUIPMENT
Turbine Drive Transmission \* 325 Horsepower Wildent 445 Engine \* Heater and
Defroster \* Rear Seat Speaker \* FoamPadded Seats—Front and Rear \* Electric
Clock \* Deluce Steering Wheel \* Automatic Trunk Light \* License Plate Frame
\* Aluminum Front Birake Drums \* Fullflow Oil Filter \* Re-usable Air cleaner
Element \* Electric Windshed Wippers Element \* Electric Windshield Wipers \* Step-On Parking Brake \* Instrument Panel Safety Pad \* Directional Signals \* Glove Compartment Light \* Smoking Seit \* Rear Seat Ash Trays \* Dani Sun Rear Seit \* Got St Tubeless Tres \* All Vinyl Front Bucket Seats \* Foam Rubber Headlining \* Center Console \* Tachomicter \* Console-mounted Transmission \* Wheel Cores \* Custom Top Covering \* Rear Floor Area Courtey Light (mounted at rear of console) \* Dual Eshaust \* Dual Honn \* Full 13-in. Wheels \* Single Key Looking Systom \* Key Starling \* Crank-Courtey Wildcat Exterior Trim \* Distinctive Wildcat Exterior Trim \* OPTIONS \* AND ACCESSORIES\* OPTIONS AND ACCESSORIES

Power Steering . Sonomatic Radio and Manual Antenna . Sonomatic Radio with Electric Antenna . Wonderbar Radio with Manual Antenna • Wonderbar Radio with Electric Antenna \* Safety Group (Back up Lights, Glare Proof Mirror, Parking Brake Signal Light, Salety Buzer, Trip Odometer and Courtesy Lights) \* Windshield Washer—Dual Speed Wiper \* Soft Ray Tinted Glass (Windshield Only) \* Power Brakes \* Soft Ray Tinted Glass (all windows) \* Deluxe Handy Mats \* Deluxe Carpet Saver \* Carpet Covers \* Trunk Mat \* Air Conditions \* Chrome Door Control Side New Mirror \* Whitewall Tites \* Oversize Whitewall Tites \* Oversize Whitewall Tites \* Oversize Blackwall Tites \* Power Windows \* Washer \* Oversize Blackwall Tites \* Power Windows \* Control Side \* Oversize Whitewall Tites \* Power Windows \* Oversize Blackwall \* Oversize Flectric Antenna . Safety Group (Raci Tires \* Oversize Whitewall Tires \* Over-size Blackwall Tires \* Power Windows \* Positive Crankcase Ventilation \* Guide Matic \* Positive Traction Differential \* Automatic Trunk Release \* Gas Tank Door Guard \* Compass \* Tissue Dispenser \* Spotlamp \* Rear Window Defroster \* Outside Rearview Mittor \* Vision Vanity Mittor \* Map Case Package \* Seat Belts

Engine: Wildcat 445; Type: 90°V8; Displacement, cu. in.: 401; Horsepower & 4400 R.P.M.: 325: Max. Torque: 445 @ 2800 R.P.M.: Compression Ratio: 10.25 to I: Carburetor: 4-Barrel; Transmission: Turbine Drive. Engine lubricating System: Main bearings, connecting rods and camshaft bearings pressure lubricated. Piston pins splash lubricated. Cylinder walls splash and nozzle lubricated. Normal oil pressure 40 @ 1600 r.p.m. Full-flow oil filter standard on all models. Crankcase capacity (refill less filter): 4 quarts. Fuel System: Four-barrel carburetor. Standard automatic choke. Mechanical fuel pump. Two stage gasoline filter with fine filter in fuel tank and extra-fine filter at the carburetor. Oilimpregnated polyurethane air cleaner. Exhaust-type intake manifold heat control. Twenty-gallon fuel capacity. Engine Cooling: Pressure system. Choke-type circulation thermostat. Centrifugal water pump. Capacity: 18.5 quarts with heater. Exhaust System: Single muffler for both banks of cylinders is mounted crosswise to the frame. Heavy zinc and aluminum coatings of muffler parts promote long life. Dual exhaust standard. Electrical: Twelve-volt electrical system, Five-position starter-ignition switch. Transmission: Turbine Drive standard. Turbine Drive is a torque converter type of transmission, fully auto-matic with two turbines, a variable pitch stator and a fixed-vane stator. Maximum torque ratio in DRIVE range at stall, 3.4 to 1. Total oil capacity (refili): 12 quarts. Propeller Shaft: Hide-Away Drive Shaft is slightly angled to reduce tunnel height in rear seat. Angled sections are connected by a special constant-velocity universal joint that insures vibrationless transfer of power to rear axle. Shaft is connected to transmission and rear axle by needle bearing universal snat is connected to transmission and rear axis by needle bearing universal joints. Rear Axie: Hypoid gearts, semi-floating. Gear ratios with Wildcat 445, 3.23 to 1. Rear wheel bearings permanently lubricated. Transfer of driving forces through rubber-mounted arms connected to frame. Positive traction differential optional. Frame: Safety-X-Frame with box section cross-members and tubular center section through which propeller shaft passes. Extra-heavy body side rails add extra strength. Suspension: Independent ball-joint front suspension with track bar. Coal springs front and rear. Rear springs loaded through lower control arms. Direct acting hydraulic shock absorbers front and rear. New suspension geometry means there's no "squat" when you start, no "dive" when you stop. Brakes: Hydraulic, self energizing. Air-cooled finned, aluminum brake drums front; finned cast iron drums rear. Total lining area: 197.32 sq. in. Step-On parking brake operating through rear service brake shoes. Power brakes optional. Wheels and Tires Disc-type wheels. Size 6.00° x 15°, "L"-type flange. Tires: 7.60° x 15°; Oversize tires optional, Whitewall tires optional. Steering: Easy Power Steering optional. Overall ratio: 20.7 to 1. Flexible coupling in power gear screens out vibration. Exterior Dimensions: Overall Length: 214.1\*; Overall Width: 77.9\*; Overall Height: 56.4°; Wheelbase: 123.0°; Tread—Front: 62.0°; Tread—Rear: 61.0°. Interior Dimensions: Leg Room, Front: 44.5°; Leg Room, Rear: 38.8°; Head Room, Front: 37.8"\*; Head Room, Rear: 38.3"\*; Shoulder Room, Front: 58.9";

### THINGS YOU SHOULD KNOW ABOUT THE BUICK SKYLARK CONVERTIBLE



190 Horsepower Skylark Aluminum V-8 • 3-Speed Synchromesh Transmission • Heater and Defroster . Re-usable Air Cleaner Element . Electric Windshield Wipers . Directional Signals . All Vinyl Front Bucket Seats . Dual Sliding Sun Shades . Foam-padded Seats-Front and Rear . Cigarette Lighter . Magic Mirror Finish . Custom Bright Exterior Moldings . Full Instrument Panel Safety Padding . Paddle-type Arm Rests . Skylark Super Deluxe Wheel Covers . Skylark Steering Wheel . Rear Passenger Compartment Courtesy Lights . Ash Tray and Glove Compartment Lights . Full Carpeting . Power operated Top • Five 6.50 x 13 Tubeless Tires • Duas Horns . Single Transverse muffler . Key Starting . Single-key Locking System.

### OPTIONS AND ACCESSORIES

Dual-Path Turbine Drive Transmission • 4-Speed Synchromesh Transmission • Power Steering . Radio with Manual Antenna . Convenience Group (Glare Proof Mirror and Electric Clock) . Windshield Washer-Dual Speed Wipers . Back-Up Lights . Soft Ray Tinted Glass (Windshield only) . Power Brakes . Air Conditioner, Cool Pack . Cool Pack Air Conditioner Modification • Chrome Door Guards . Remote Control Side View Mirror . Whitewall Tires . Oversize Whitewall Tires (7.00 x 13) . Oversize Blackwall Tires (7.00 x 13) . Power Windows . Positive Crankcase Ventilation · Positive Traction Differential · Gas Tank Door Guard . Compass . Litter Basket . Tissue Dispenser . Spot Lami · Outside Rear View Mirror · Visor Vanity Mirror • Seat Belts • Deluxe Handy Mats . Deluxe Carpet Saver

### SPECIFICATIONS

Skylark Aluminum V8 Engine: 90 degree V8, valve-in-head type, Cylinder block, cylinder head, pistons, intake manifold, timing chain cover, water pump cover, and many smaller parts of aluminum alloy. Cast iron cylinder liners. Displacement 215 cu. in Compression ratio 11.0 to 1. Horsepower, 190 @ 4800 rpm, Maximum torque 235 foot pounds @ 3000 rpm, Firing order: 1-8-4-3-6-5-7-2 Splash and pressure lubrication system Crankcase capacity, 4 quarts (refill less filter). Normal oil pressure 33 (e 2400 rpm. Full-flow oil filter standard. Fourbarrel carburetor. Mechanical fuel pump. Water intake manifold heat control. Pressure liquid cooling system. Centrifugal water pump. Cooling system capacity: 13.5 quarts with heater. Twelve-volt electrical system. Five-position starterignition, Transmission: Three-speed synchromesh transmission standard. 4-speed synchromesh optional at extra cost. Dual-Path Turbine Drive Transmission optional at extra cost. In Dual-Path transmission approximately 64 per cent of driving effort transferred hydraulically and 36 per cent mechanically after upshift. Transmission is fully automatic with a "down-shift" for passing in the 18-55 mph. range. Propeller Shaft: Hide-Away Drive Shaft is slightly angled to reduce tunnel height. Angled sections are connected by a special constant-velocity universal joint that insures vibrationless transfer of power to the rear axle. Shaft is connected to transmission and rear axle by needle-bearing universal joints. Rear Axle: Hypoid gears, semi-floating. Gear ratio: 3.36 to 1. Rear wheel bearings permanently lubricated, Body and Frame: Fully unitized body with integral body-frame construction. Suspension: Independent ball-joint front suspension Four link rear suspension. Coil springs front and rear. Rear springs are loaded through lower control arms. Direct-acting, hydraulic shock absorbers front and rear. Driving forces from axle to body-frame are through rubber-bushed rear links. Brakes: Air cooled cost iron brake drums front and rear. Total lining area, 129.87 sq. in. Pull-type parking brake operating through rear service brake shoes. Power brakes optional at extra cost, Steering: Manual recirculating ball steering. Overall ratio, 26.18 to 1. Power steering optional. Overall ratio 20.8 to 1. Wheels and Tires: Disc-type wheels. Size 4.50" x 13", "J" type flange. Tire size: 6.50" x 13". White sidewall tires are optional at extra cost. Dimensions: Overall Length: 188.4"; Overall Width: 70.3"; Overall Height: 52.1"; Wheelbase: 112.1"; Tread, Front: 56.0°; Tread, Rear: 56.0°; Leg Room, Front: 44.3°; Leg Room, Rear: 35.6"; Head Room, Front: 39.0"\*; Head Room, Rear: 37.2"\*; Shoulder Room, Front: 55.2"; Shoulder Room, Rear: 53.2".

BUICK MOTOR DIVISIOR, GENERAL MOTOPS CORPORATION, RESERVES THE RIGHT TO MAKE CHANGES, AT ART TIME, WITHOUT MOTICE IN PRICES, COLORS, MATERIALS, EQUIPMENT, SPECIFICATIONS AND MODELS, AND ALSO TO DISCONTINUE MODELS

BUICK MOTOR DIVISION . GENERAL MOTORS CORPORATION . FLINT 2, MICHIGAN

