





the Jeepster





SPECIFICATIONS.

GENERAL

Wheelbase 104" 1781/2" Overall length Road clearance

8 5/16" (Regraxle)

ENGINE

No. of cylinders 63 HP @ 4000 RPM

Horsepower 31/4"

Bore 43/4" Stroke Torque 106 lb. ft. at 2000 RPM

Displacement 134.2 cu. in. 8.5" diam., 72 sq. in. Clutch engagement area

Compression ratio (Standard) 6.48 to 1

Positive crankcase ventilation Cooling system

Closed cooling system with pressure cap and thermostat-more than adequate

for all climates REAR AXLE RATIO 4.88 to 1

FRONT SUSPENSION Independent, planar type SPRINGS

All mounted in rubber

Front Rear

Transverse, semi-elliptic Conventional, semi-elliptic Rubber inserts insure silent spring action and controlled

shock absorber action. TIRE SIZE

FRAME

5.90-15, 4-ply Super Cushion, white side-walls

BRAKES, SERVICE 133 sq. in. OVERDRIVE Reduces engine revolutions

30%

Box section frame with "X" reinforcement

STANDARD EQUIPMENT ON THE 'JEEPSTER', AT NO EXTRA COST, ARE THE FOLLOWING FEATURES:

Overdrive transmission Vacuum booster type fuel pump Front bumper guards

Deluxe steering wheel and Luxurious pipe trim upholstery horn ring

Dual windshield wipers Wheel trim rings Dual sun visors Dual horns Inside rear view mirror Locking glove box

Saecifications subject to change without notice.