


Standard Equipment: XH II Falcon Longreach Utes and Van



FEATURES:

MECHANICAL

- 4.0 litre OHC engine with multi-point electronic fuel injection.....
- 4.0 litre high performance engine with multipoint electronic fuel injection.....
- 5.0 litre V8 engine and 4 speed T-bar auto transmission.....
- 5.0 litre high performance V8 engine.....
- Electronic engine control (EEC IV) system.....
- Electronic engine control (EEC V) system.....
- 5 speed manual floor shift transmission.....
- 4 speed electronic T-Bar automatic.....
- 4 speed electronic column shift automatic.....
- Power assisted rack and pinion steering.....
- Short and long arm front suspension.....
- Hotchkiss rear suspension.....
- Front stabiliser bar.....
- Four wheel disc brakes.....
- Heavy duty rear suspension.....
- Sports suspension.....

EXTERIOR


- Body coloured front and rear bumpers.....
- Front bumper inserts
 - Black.....
 - Body colour.....
- Front bumper inserts.....
- Bodyside protection mouldings
 - Black.....
 - Red (i).....
- Exterior rear view mirrors - power
 - Black.....
 - Body colour.....
- Tonneau cover.....
- Locking fuel cap.....
- Centre caps.....
- 15 x 6 JJ steel wheels with P205 / 65 HR 15 tyres.....
- 15 x 7 JJ alloy wheels with P225 / 60 ZR 15 tyres.....
- 15 x 7 JJ alloy XR wheels with P205 / 65 HR 15 tyres.....
- 16 x 7 JJ alloy open face XR wheels with P225 / 50 ZR 16 tyres.....
- 15 x 6 JJ steel wheels with P205 / 75 8 ply tyres.....
- Polycarbonate halogen headlamps with integrated indicator and park lamps.....
- Quad headlamps and clear front quarter parking lights.....
- Two speed and intermittent wiper, demand wash / wipe and demand wipe.....
- Two speed and variable intermittent wiper, demand wash / wipe and demand wipe.....
- Dual jet windscreen washers.....
- Tinted windscreen sideglass, fixed quarter and backlite.....
- Tinted glass in bodyside and rear doors.....
- Drop down tailgate with levelling cable.....
- Split rear barn doors.....
- Lock down radio aerial.....
- Winch mounted spare wheel (excluding LP Gas).....

INTERIOR

- Smart lock electronic engine immobilisation, keyless entry system and central locking.....
- High security locking system featuring "Tibbe" locks on doors and ignition and strengthened steering column lock housing.....
- Rear window demister with timed automatic switch off feature.....
- Driver airbag.....
- Soft feel four spoke steering wheel.....
- Leather wrapped steering wheel.....
- Adjustable rake and reach steering wheel.....
- Prismatic day / night interior rear view mirror.....
- Lidded stowage bin (with bucket seats only).....
- Digital clock in radio.....
- Door map pockets.....
- Padded cloth armrest.....
- Driver's left footrest.....
- Ignition lock illumination.....
- Moulded vinyl sunvisors.....
- Rubber matted floor covering (b).....

	Longreach GLi Ute	Longreach S Ute	Longreach XR6 Ute	Longreach XR8 Ute	Longreach Outback Ute	Longreach GLi Van
4.0 litre OHC engine with multi-point electronic fuel injection.....	•	•			•	•
4.0 litre high performance engine with multipoint electronic fuel injection.....			•			
5.0 litre V8 engine and 4 speed T-bar auto transmission.....		OPT				
5.0 litre high performance V8 engine.....				•		
Electronic engine control (EEC IV) system.....	•	•			•	•
Electronic engine control (EEC V) system.....	•	•	•	•	•	•
5 speed manual floor shift transmission.....	•	•	•	•	•	•
4 speed electronic T-Bar automatic.....	OPT	OPT	OPT	OPT		OPT
4 speed electronic column shift automatic.....	OPT				OPT	OPT
Power assisted rack and pinion steering.....	•	•	•	•	•	•
Short and long arm front suspension.....	•	•	•	•	•	•
Hotchkiss rear suspension.....	•	•	•	•	•	•
Front stabiliser bar.....	•	•	•	•	•	•
Four wheel disc brakes.....	•	•	•	•	•	•
Heavy duty rear suspension.....	OPT				•	OPT
Sports suspension.....		OPT	•	•		
Body coloured front and rear bumpers.....	•	•	•	•	•	•
Front bumper inserts <ul style="list-style-type: none"> - Black..... - Body colour..... 	•	•	•	•	•	•
Front bumper inserts.....	•	•	•	•	•	•
Bodyside protection mouldings <ul style="list-style-type: none"> - Black..... - Red (i)..... 	•	•	•	•	•	•
Exterior rear view mirrors - power <ul style="list-style-type: none"> - Black..... - Body colour..... 	•	•	•	•	•	•
Tonneau cover.....	•	•	•	•	•	•
Locking fuel cap.....	•	•	•	•	•	•
Centre caps.....	•	•	•	•	•	•
15 x 6 JJ steel wheels with P205 / 65 HR 15 tyres.....	•	•	•	•	•	•
15 x 7 JJ alloy wheels with P225 / 60 ZR 15 tyres.....		•				
15 x 7 JJ alloy XR wheels with P205 / 65 HR 15 tyres.....		OPT (i)	OPT	•		
16 x 7 JJ alloy open face XR wheels with P225 / 50 ZR 16 tyres.....				•		
15 x 6 JJ steel wheels with P205 / 75 8 ply tyres.....					•	
Polycarbonate halogen headlamps with integrated indicator and park lamps.....	•	•			•	•
Quad headlamps and clear front quarter parking lights.....			•	•		
Two speed and intermittent wiper, demand wash / wipe and demand wipe.....	•				•	•
Two speed and variable intermittent wiper, demand wash / wipe and demand wipe.....	•	•	•	•	•	•
Dual jet windscreen washers.....	•	•	•	•	•	•
Tinted windscreen sideglass, fixed quarter and backlite.....	•	•	•	•	•	•
Tinted glass in bodyside and rear doors.....	•	•	•	•	•	•
Drop down tailgate with levelling cable.....	•	•	•	•	•	•
Split rear barn doors.....	•	•	•	•	•	•
Lock down radio aerial.....	•	•	•	•	•	•
Winch mounted spare wheel (excluding LP Gas).....	•	•	•	•	•	•
Smart lock electronic engine immobilisation, keyless entry system and central locking.....	•	•	•	•	•	•
High security locking system featuring "Tibbe" locks on doors and ignition and strengthened steering column lock housing.....	•	•	•	•	•	•
Rear window demister with timed automatic switch off feature.....	•	•	•	•	•	•
Driver airbag.....	OPT	OPT	OPT	OPT	OPT	OPT
Soft feel four spoke steering wheel.....	•	•	•	•	•	•
Leather wrapped steering wheel.....	•	•	•	•	•	•
Adjustable rake and reach steering wheel.....	•	•	•	•	•	•
Prismatic day / night interior rear view mirror.....	•	•	•	•	•	•
Lidded stowage bin (with bucket seats only).....	•	•	•	•	•	•
Digital clock in radio.....	•	•	•	•	•	•
Door map pockets.....	•	•	•	•	•	•
Padded cloth armrest.....	•	•	•	•	•	•
Driver's left footrest.....	•	•	•	•	•	•
Ignition lock illumination.....	•	•	•	•	•	•
Moulded vinyl sunvisors.....	•	•	•	•	•	•
Rubber matted floor covering (b).....	•	•	•	•	•	•

Standard Equipment: XH II Falcon Longreach Utes and Van



FEATURES:

INTERIOR (Continued)

	Longreach GLi Ute	Longreach S Ute	Longreach XR6 Ute	Longreach XR8 Ute	Longreach Outback Ute	Longreach GLi Van
Spun yarn cut pile Luna Mist floor covering		•	•	•	•	
Carpeted rear bulkhead and moulded cloth covered headlining	•	•	•	•	•	•
Bucket seats and floor console	•	•	•	•	•	•
– 5 speed manual						
– 4 speed T'bar automatic	OPT	OPT				OPT
Sports bucket seats and floor console						
– 5 speed manual						
– 4 speed T'bar automatic			OPT	OPT		
Bucket seats and third passenger centre cushion – 5 speed manual	OPT					
Centafold bench seat for three passengers and 4 speed column automatic	OPT				OPT	OPT
Driver and passenger lumbar support (bucket seats only)	•	•	•	•	•	•
Driver and passenger seat recline adjustable (bucket seats)	•	•	•	•	•	•
Driver height front / rear of cushion adjustable	•	•	•	•	•	•
Height adjustable headrests	•	•	•	•	•	•
Door activated courtesy light	•	•	•	•	•	•
Adjustable instrument panel illumination	•	•	•	•	•	•
Illuminated and lockable glove box	•	•	•	•	•	•
Cigarette lighter and ashtray	•	•	•	•	•	•
Four speed fan boosted ventilation	•	•	•	•	•	•
Electronic tuning AM/FM stereo radio/cassette with two speaker system	•				•	•
Electronic tuning AM/FM stereo radio/cassette with four 20 watt speaker system		•	•	•		
Gauges: Speedometer, tachometer, LCD odometer / tripmeter, service indicator, fuel level and water temperature	•				•	•
Gauges: Speedometer, tachometer, LCD odometer / tripmeter, service indicator, fuel level and water temperature, oil pressure and battery voltage		•	•	•		
Warning lights: High beam, low oil pressure, lamps "on" alternator, brake failure, park brake "on", low fuel, high temperature, security, seat belts, (ABS airbag and cruise control where appropriate), economy mode indicator (auto trans)	•	•	•	•	•	•
Audible warnings: Turn signals, lights "on" and high engine temperature	•	•	•	•	•	•
Warning lights additional: Heated rear window, low coolant and low washer fluid	•	•	•	•	•	•
Audible warning additional: Low oil pressure	•	•	•	•	•	•
Seat belts with belt lockers (outboard seats only)	•	•	•	•	•	•
Single horn	•	•	•	•	•	•
Dual horns	•	•	•	•	•	•
Interior dome light time delay entry and exit	•	•	•	•	•	•

TVE LP GAS Option

- Available on 6 cylinder GLi and S utes and GLi van (manual and automatic). Engineered in compliance with Australian Standard 1425 (1989).
- No discernible difference in driveability.
- LPG tank mounted high up beneath the load tray and does not affect ground clearance or departure angle.
- LPG tank capacity 68 litres (useable).
- Uses one fuel gauge – for both petrol and LPG.
- Spare wheel mounted horizontally in load area.

- LPG tank filler is bracketed through rear bumper.
- LPG supply is preshaped with anti-corrosive coatings.
- "Closed Loop" system adjusts gas supply to ensure efficient, clean burning of fuel.
- To change between petrol and LPG there is a Pull-Pull switch mounted in lower dashboard area. An LED switch is lighted when LPG in use.
- Vehicle's original petrol fuel tank is retained in the same position.

Longreach Outback

- Heavy duty 3.45 : 1 rear axle features BTRE "Hydratrak" limited slip differential which increases torque to the slower rotating wheel and progressively increases useable traction.
- 6.5 x 15" steel wheels are fitted with durable Firestone 205 x 75 8 ply off-road tyres.
- Rear suspension features heavy duty dual rate springs with raised ride height plus heavy duty springs at front.
- Dual fuel tanks with central changeover valve – total capacity 126 litres
- Heavy duty gas shock absorbers have a 20% larger diameter providing high temperature stability
- Cyclonic heavy duty two stage air filter with automatic dust extraction.
- Heavy duty sump and transmission guard made of 2.5mm plate.
- Anti-abrasion shield fitted to lower edge of front bumper.
- Outback's ground clearance has been increased to 200mm.
- Stronger thick wall steel wheel designed to meet full life durability at one tonne rating.
- Load proportioning valve gives consistent braking effort in both laden and unladen conditions.
- One tonne load capacity (k).

Specifications – FORD FALCON XH II LONGREACH UTES AND VAN

Engine	4.0 Litre	5.0 Litre	4.0 Litre XR6	5.0 Litre XR8
Power (DIN kW)	148kW @ 4900rpm	165kW @ 4500rpm	164kW @ 5000rpm	185kW @ 4500rpm
Torque (DIN Nm)	353Nm @ 3000rpm	388Nm @ 3000rpm	366Nm @ 3500rpm	402Nm @ 3100rpm
Cylinder head	Aluminium Alloy OHV	Cast Iron OHV	Aluminium Alloy OHV	Cast Iron OHV
Cylinders	6 in line	V8	6 in line	V8
Fan	Twin thermatic	Twin thermatic	Twin thermatic	Twin thermatic
Bore (mm)	92.26	101.6	92.26	101.6
Stroke (mm)	99.3	76.2	99.3	76.2
Capacity	3984	4942	3984	4942
Compression ratio	9.3 : 1	9.0 : 1	9.35 : 1	9.0 : 1

Transmission Ratios

	1st	2nd	3rd	4th	5th	Rev	Final Drive	Final Drive Ratio for Outback, 1 Tonne Manual and XR is 3.45 : 1.
Manual	3.25	1.99	1.29	1.00	0.72	3.15	3.23 : 1	Limited Slip Differential standard on SV8, XR6 and XR8.
Automatic	2.39	1.45	1.00	0.68		2.09	3.23 : 1	"Hydratrak" Limited Slip Differential Axle is standard on Outback.

Suspension

Front	Rear
• Short and Long Arm Spindle (SLALS) design	• Rigid axle
• Single rate coil springs	• Hotchkiss suspension
• Twin tube telescopic shock absorbers mounted coaxially within the coil spring	• 6-leaf springs
• Stabiliser bar	• Twin tube telescopic shock absorbers
	• Dual rate leaf springs with one tonne option

XR6 and XR8 Handling Suspension: Incorporates uprated springs with lower ride height and uprated shock absorbers

Brakes

Front:	Power assisted ventilated disc : 287 mm
Rear:	Power assisted disc 299mm

Steering

	Longreach GLi Ute	Longreach S Ute	Longreach XR Ute	Longreach Outback Ute	Longreach GLi Van
Rack and Pinion steering gear					
Turning Circle (diameter)	11.3m	11.3m	11.3m	11.3m	11.3m

Dimensions

	Longreach GLi Ute	Longreach S Ute	Longreach XR Ute	Longreach Outback Ute	Longreach GLi Van
Exterior (mm)					
Overall length	4959	4959	4959	4959	4959
Overall height	1440	1440	1417	1470	1670
Overall width (h)	1862	1862	1862	1862	1862
Wheelbase	2923	2923	2923	2923	2923
Front track	1566	1566	1566	1566	1566
Rear track	1546	1546	1546	1546	1546
Front overhang	919	919	919	919	919
Rear overhang	1117	1117	1117	1117	1117
Interior (mm)					
Front headroom	965	965	965	965	965
Front leg room	1080	1080	1080	1080	1080
Front shoulder room	1508	1508	1508	1508	1508
Front hip room	1412	1412	1412	1412	1412
Load Area (mm)					
Max load length	– Tailgate down 2696	2696	2696	2696	N/A
	– Tailgate up/door closed 2134	2134	2134	2134	2134
Width	1530	1530	1530	1530	1530
Width (b/w wheel arches)	1140	1140	1140	1140	1140
Width (b/w tailgate latches)	1330	1330	1330	1330	N/A
Tailgate height	410	410	410	410	N/A
Van barn door width – (b/w lower hinges)	N/A	N/A	N/A	N/A	1325
– (level with drip rail)	N/A	N/A	N/A	N/A	1080
Maximum height	N/A	N/A	N/A	N/A	1005
– (floor to roof load area)	N/A	N/A	N/A	N/A	925
– (at rear incl top door hinge)	N/A	N/A	N/A	N/A	925
Cubic capacity	1.1m ³	1.1m ³	1.1m ³	1.1m ³	2.8m ³

Fuel Tank Capacity

	Petrol	LP Gas (Useable)
Longreach GLi, S, XR6 and XR8	68 litres	68 litres – where fitted to 6 cyl GLi & S models
Longreach Outback Ute	126 litres	N/A

Load Capacity

	Kerb		GVM 6 Cyl and V8	Load Capacity	
	6 Cyl	8 Cyl		6 Cyl	V8
GLi Ute manual / 1 tonne option	1480		2300 / 2620	820 / 1140	
GLi ute Automatic / 1 tonne option	1510		2300 / 2670	790 / 1160	
GLi Van Manual / 1 tonne option	1520		2300 / 2690	780 / 1170	
GLi Van Automatic / 1 tonne option	1550		2300 / 2670	750 / 1120	
S Ute Manual	1480		2300	820	
S Ute Automatic	1510	1530	2300	790	770
XR Ute Manual	1495	1525	2055	560	530
XR Ute Automatic	1525	1555	2055	530	500
Outback Manual (k)	1480		2620	1140	
Outback Automatic (k)	1510		2620	1110	

Gross Combined Mass (GCM)

Total Vehicle and Trailer – 4190kg (3945kg for XR6 and XR8)

Options – FORD FALCON XH II LONGREACH UTES AND VAN

Engine Transmission Combinations

	Longreach GLi Ute	Longreach S Ute	Longreach XR6 Ute	Longreach XR8 Ute	Longreach Outback Ute	Longreach GLi Van
4.0 litre 5 speed manual	STD	STD	N/A	N/A	STD	STD
4.0 litre 4 speed column auto (a)	OPT	N/A	N/A	N/A	OPT	OPT
4.0 litre 4 speed T-Bar auto (b)	OPT	OPT	N/A	N/A	N/A	OPT
4.0 litre High Performance 5 speed manual	N/A	N/A	STD	N/A	N/A	N/A
4.0 litre High Performance 4 speed T-Bar auto	N/A	N/A	OPT	N/A	N/A	N/A
5.0 litre 4 speed T-Bar auto	N/A	OPT	N/A	N/A	N/A	N/A
5.0 litre High Performance 5 speed manual	N/A	N/A	N/A	STD	N/A	N/A
5.0 litre High Performance 4 speed T-Bar auto	N/A	N/A	N/A	OPT	N/A	N/A

Convenience

	Longreach GLi Ute	Longreach S Ute	Longreach XR6 Ute	Longreach XR8 Ute	Longreach Outback Ute	Longreach GLi Van
Towpack (c)						
– 1600 kg	OPT	OPT	OPT	OPT	OPT	OPT
– 2300 kg †	OPT	OPT	OPT	OPT	N/A	OPT
Electronic cruise control (f)	OPT	OPT	OPT	OPT	OPT	OPT
Air conditioning	OPT	OPT	OPT	OPT	OPT	OPT
Anti-lock brakes (g)	OPT	OPT	OPT	OPT	N/A	OPT
Driver's airbag	OPT	OPT	OPT	OPT	OPT	OPT
Limited slip differential (g) (m)	OPT	OPT	STD	STD	STD	OPT
LPG (j)	OPT	OPT	N/A	N/A	N/A	OPT
Prestige paint (e)	OPT	OPT	OPT	OPT	OPT	N/A
One tonne payload	OPT	N/A	N/A	N/A	STD (k)	OPT
Heavy duty one tonne payload	OPT	N/A	N/A	N/A	N/A (k)	OPT
Centafold bench seat with column automatic (a)	OPT	N/A	N/A	N/A	OPT	OPT
Three seat with manual transmission	OPT	N/A	N/A	N/A	STD	N/A
Vinyl trim (d)	OPT	N/A	N/A	N/A	N/A	OPT
16 x 7J alloy wheels with P225 / 50 ZR 16 tyres	N/A	OPT (l)	OPT	STD	N/A	N/A
Momo sports steering wheel	N/A	N/A	OPT	OPT	N/A	N/A
Bullbar	OPT	OPT	N/A	N/A	OPT	OPT
Body styling kit	OPT	OPT	OPT	OPT	N/A	OPT
Sports suspension	N/A	OPT	STD	STD	N/A	N/A

Towing

† A Ford approved 2300kg capacity Class II towbar is available from Ford Dealers for vehicles fitted with automatic transmission (except Outback). However, the Class II tow bar is not compatible with vehicles fitted with LPG units.

OPT – Optional at extra cost. STD – Standard equipment. N/A Not available.

About this specification sheet: This sheet is designed to provide you with selected specification data for the Ford Products which have been described in a general way in the relevant brochure. Because of changes in conditions and circumstances Ford reserves the right, subject to all applicable laws, at any time, at its discretion, and without notice to discontinue or change the features, designs, materials, colours and other specifications, and the prices of its products, and to either, permanently or temporarily with draw any such products from the market without incurring any liability to any prospective purchaser or purchaser. Because of variations which occur in manufactured products, all capacities, measurements, dimensions and weights quoted in the relevant brochure and this specification sheet should be taken as approximate only. Always consult an Authorised Ford Dealer for the latest information with respect to features, specifications, prices, optional equipment and availability before deciding to place an order.

FORD MOTOR COMPANY OF AUSTRALIA LIMITED
ACN 004 116 223
Registered Office: 1735 SYDNEY ROAD CAMPBELLFIELD VIC 3061
PRINTED SEPTEMBER 1997



Footnotes

(a) Centafold bench seat is standard on Falcon GLi and Outback Ute and GLi Van when a column shift automatic is ordered. Centafold is not available with a floor shift transmission and centre console.

(b) Floor carpet on Falcon GLi Ute and Van is available when T-Bar automatic transmission with centre console is specified.

(c) Towing capacity subject to State and Territory regulations.

The Towing Pack is a factory-fitted option and provides a towing capacity of 1600kg when used in conjunction with a suitable caravan or trailer braking system and towing equipment. This pack consists of:

- Tow bar
- Gooseneck
- Wiring harness with 7 pin electrical connector
- Transmission oil cooler (automatic transmissions only)
- Provision for electric trailer brakes is pre-wired into every Longreach vehicle (see Dealer for details)

NOTE: The caravan or trailer braking system and any other items (such as the tow ball, load levelling devices and safety chains) required for the attachment of a trailer, caravan or the like to the vehicle are not supplied as part of the Pack, and must be purchased at extra cost or be supplied by the purchaser of the vehicle.

The Towing Pack is designed to be incorporated in the vehicle during the assembly of the vehicle. The actual towing capability and performance of a vehicle will depend upon many factors including the suitability of the caravan, trailer, etc, the condition of the vehicle, the vehicle load, the vehicle specifications (including engine capacity, transmission type, axle ratio, tyre type and size), weather conditions, road gradient, terrain and other prevailing conditions.

A towing accessory is also available for fitment from your Authorised Ford Dealer. A Ford-approved transmission oil cooler must be fitted in conjunction with any towing accessory fitted to automatic vehicles and used to tow a gross weight of more than 500kg. Consult your Authorised Ford Dealer for the latest information with respect to the specifications and the availability of this accessory towing pack.

(d) Vinyl seat trim is available in both bucket and centafold seat configurations.

(e) Consult the Ford colour selector or your Authorised Ford Dealer to determine which colours are available in metallic paint.

(f) Cruise control available for all models including column auto transmission.

(g) LSD is mandatory with ABS option, but not on GLi and S utes or GLi Van with 3.23 : 1 rear axle ratio.

(h) Overall width excludes exterior mirrors.

(i) Red XR Ute has black bodyside protection mouldings.

(j) Addition of LPG option will reduce ride height by 12mm on 1/2 tonne utes and van and by 20mm on 1 tonne utes and van. LPG optional on 6 cyl 5 model only – N/A 8 cyl.

(k) Falcon Longreach Outback model is rated at one tonne load capacity. NOTE: If the vehicle is driven off road in harsh conditions for extended periods of time, loads of greater than 750kg should not be carried.

(l) P225 / 50 ZR16 tyres on Falcon S can only be fitted with sports suspension.

(m) LSD is mandatory with V8.