# Zephyr-Six

The car for moderns on the move



## SPECIFICATIONS ZEPHYR-SIX SEDAN

#### ENGINE

Six cylinder cast integrally with upper half of crankcase; bore 3.25 ins.; stroke 3.13 ins. Capacity 155.8 cu. ins. Overhead valves, push rod operated from harmonic cams in cylinder block. Compression ratio 6.9:1. B.H.P. 80 at 4,200 R.P.M. Torque 128 lbs./ft. at 2,000 R.P.M. Four bearing crankshaft with integral weights, dynamically balanced. Detachable cast-iron cylinder head incorporating volume controlled combustion chambers for economy and smooth running. Special autothermic alloy pistons. Three point suspension of engine and gear box giving remarkably smooth power flow.

#### ENGINE LUBRICATION

Pressure feed by submerged gear pump to crankshaft main bearings. ressure reed by submerged gear pump to crankshaft main bearings, big-end bearings and camshaft bearings via drillings in cylinder block and crankshaft. Full flow type oil filter fitted direct to cylinder block. Accessible dip stick and oil filter. Sump capacity with oil filter 8.5 pints.

#### IGNITION

12 volt battery and coil (battery accessibly located under hood) — distributor has automatic advance and retard and additional vacuum control. Sparking plug size 14 mm. Firing order 1, 5, 3, 6, 2, 4,

#### FUEL SYSTEM

Diaphragm type fuel pump mechanically operated. Down draught carburettor has special choke control and is fitted with combined air cleaner and silencer. Electrical petrol gauge. Petrol tank at rear, capacity 10.5 gallons.

#### COOLING SYSTEM

Belt-driven fan and water pump with thermostatic heat control. Tube and fin type radiator. Capacity of system 22 pints.

#### TRANSMISSION

Clutch - dry, single plate, spring cushioned. Hydraulic operation from pedal to heavy duty, ball-bearing thrust release. Remote control of gears on steering column, Light action synchro-mesh on top and second gears. Helically cut constant mesh gears. Three forward speeds. Overall ratio — 3.90 to 1, 6.40 to 1, and 11.08 to 1. Reverse 15.06 to 1. Oil capacity of gearbox 2.5 pints approximately.

3/4 floating, hypoid final drive. Heavy duty roller and ball bearings. Open type drive shaft. Universal joints have needle roller bearings.

Axle ratio — 3.90 to 1. Oil capacity 2½ pints approximately.

#### FRONT SUSPENSION

excellent riding and steering.

incomparation of the control arm to a tubular cross-member botted to underside of the unitary body. An anti-roll torsion bar is fitted which, being triangulated, holds the track control arms in the fore and aft direction. The wide spacing and high location of the springs and shock absorbers, combined with accurately controlled geometry, gives

#### REAR SUSPENSION

Longitudinal semi-elliptic 6 leaf springs rubber insulated. Hydraulic double-acting shock absorbers.

Hydraulic internal — front 9 ins. x 2½ ins. Rear 9 ins. x 1¾ ins. Front — two leading shoes, rear — floating expander. Total lining area 147 sg. ins. Foot brake all four wheels, handbrake on rear wheels only.

Recirculatory, ball type. Ratio 18.0 to 1. Steering wheel diameter

#### 17 ins. Two spoke safety type.

WHEELS AND TYRES Pressed steel with wide base rims. Rustless steel hub-caps. Tyres

#### 6.40 x 13.

**ELECTRICAL EQUIPMENT** Two-brush ventilated generator, compensated voltage control. Drive: "V" belt easily adjustable. Starter motor. Dual "Windtone" horns operated by horn ring on steering column. Battery: 12 volt, 57 amp. hr. at 20 hr. rate.

#### INSTRUMENTS

Conveniently grouped cluster immediately in front of driver includes speedometer, fuel gauge, ammeter, oil pressure warning light, direction indicator warning lights, ignition warning light, head-lamp main beam warning light. Instrument lighting controlled by tumbler switch on facia panel.

Choke, combined ignition-starter switch, lighting switch, instrument light and windshield wiper. Plastic control knobs. Foot operated head-lamp dimmer switch.

All-steel welded integral construction. Seating within wheelbase. Safety All-steel welded integral construction. Seating within wheelbase. Safety of glass all round. Curved type fixed windscreen and wrap-around rear window. Hinged no draught ventilations embodied in front door construction bench-type front seal. Washable vinyl headlining. Separate luggage compartment accessible from outside of car. Spare wheel housed in luggage compartment accessible from outside of car. Spare wheel housed in luggage compartment on right-hand side.

#### GENERAL FOUIPMENT

Dual windscreen wipers operated from vacuum pump fitted on engine. Moisture-proof, flush fitting hooded headlamps. Separate side lamps. Tail and stop lamps combined. Rear number plate illumination lamps. Interior light. Sun visors. Front doors lockable on both sides. Flasher Interior Iight. Jun visors, front goors lockapie on Duni sixes, treasure type direction indicators operated by self-cancelling arm on steering column. Rear view mirror. Built-in fresh air ventilation system. Provision for fitting air conditioning system, demisters and radio. Centre rear armrest.

#### GENERAL DIMENSIONS

Overall length: 14 ft. 10.5 ins. Overall width: 5 ft. 9 ins. Overall height: 5 ft. 2 ins. Wheelbase: 107 ins. Track (Front) 53 ins.; (Rear) 52 ins. Kerb Weight: 2,691 1bs.

Ford Motor Company of Australia Pty. Ltd. whose policy is one of continuous improvement, reserves the right, subject to such regulations as may from time to time apply, to change specifications and prices at any time without notice or incurring liability to purchasers.

### FORD MOTOR COMPANY OF AUSTRALIA PTY. LTD.

(Incorporated in Victoria) Registered Office: Geelong, Victoria



More Vision! Zephyr's full view wrap-around windscreen provides a greater area of unobstructed vision and highlights modern styling.




The look from the rear! Gracefully curved to blend with body lines, the new full wrap-around rear window provides wider vision and a safer view of traffic for the driver. All four corners of Zephyr are clearly seen from the driver's seat.



The seats are larger! Wider. deeper, and with a special zig-zag spring construction to keep their shape and comfort longer, the seats provide correct body support and a softer feel. A luxury feature is the centre arm-rest in the front seat.

Herald Grayure Print



bigness' greater than in many far higher priced cars. Summed up, Zephyr's interior gives you luxury and parcel shelf stretching full width behind the rear seat. beneath the facia panel on the passenger seat side, and a the glove box, there's a convenient roomy parcel tray ensure that only fresh, clean air enters the car. As well as A new type of ventilation system has a re-located intake to

column, within easy reach of the driver. ratchet-type hand brake is placed to the left of the steering steering column for easier reading and handling . . . and the All instruments and controls are grouped around the

against impact.

steering wheel is slightly 'dished' to give added protection is covered with tabric to guard against sun-glare, and the There's extra safety, too, built into Zephyr . . . the facia panel

which not only lasts longer but is easier to keep clean. armrest in the front seat, and the rich vinyl-type upholstery sleek, sweeping exterior lines. A luxury note is the centre This comfort-planned interior blends perfectly with Zephyr's

# big people.

head room there is ample space for six shoulder room, more hip room and more spaciousness. With more leg room, more tion of modern, graceful styling and The Zephyr-Six interior is a combina-



Siyled and sized for modern living

# SPECIFICATIONS ZEPHYR-SIX SEDAN

of been you may the room you need to

Recirculatory, ball type, Kaflo 18.0 to 1. Steering wheel diameter 17 ins. Two spoke safety type.

FINGINE 1. The property of the

# ENGINE LUBRICATION

Diaphragm type fuel pump mechanically operated. Down d carburettor has special choke control and is fitted with combin-cleaner and silencer. Electrical petrol gauge. Petrol tank at capacity 10.5 gailons.

# COOLING SYSTEM

Belt-driven fan and water pump with thermostatic heat control. Tube and fin type radiator. Capacity of system 22 pints.

Overall binnershous

Overall beight: 14 ft. 10.5 ins. Overall width: 5 ft. 9 ins. Overall height: 5 ft. 2 ins. Wheelbase: 107 ins. Track (Front) 53 ins.; (Rear) 52 ins. Kerb Weight: 2.691 lbs.

FORD MOTOR COMPANY OF AUSTRALIA PTY. LTD. (Incorporated in Victoria) Registered Office: Geelong, Victoria



More Vision! Zephyr's full view wrap-around windscreen provides a greater area of unobstructed vision and highlights modern styling.




fully curved to blend with body lines, the new full wrap-around rear window provides wider vision and a safer view of traffic for the driver. All four corners of Zephyr are clearly seen from the driver's seat.



provide correct body support and softer feel. A luxury feature is the

Herald Gravure Print





inird stuvero bistal

The searcs are larger! Wider, deeper, and with a special size, the searcs spring construction to keep their shape and confort longer, the seast provide correct hody support and a softer feel. A huxuy feature is the centre arm-rest in the front seat.



The look from the rear! Graceluly curved to blend with body lines, the new full wrap-around rear window provides wider wision and a window provides wider wision and a full four corners of Zephyr are All four corners of Zephyr are clearly seen from the driver's seat.



More Vision! Zephyr's full view wrap-around windscreen provides a greater area of unobstructed vision and highlights modern styling.



#### (Incorporated in Victoria) Registered Office: Geelong, Victoria

## FORD MOTOR COMPANY OF AUSTRALIA PTY. LTD.

ond motor Company of Australia Pty. Edd. whose policy is one of continuous improvement, reserves the right, subject to such regulaons as may from time to time apply, to change specifications and prices at any time without notice or incurring liability to purchasers.

GENERAL DIMENSIONS
Overall length: 14 ft. 10.5 ins. Overall width: 5 ft. 9 ins. Overall
beight: 5 ft. 2 ins. Wheelbare: 107 ins. Track (front) 53 ins.; (Rear)
52 ins. Ketb Weight: 2,697 lbs.

was abit seasode appealance for blood popular ching. Incorporate control manual control contro

abjasts all round. Curred type kiake dividustrees and wrep-storund is window. Hinged non-disuplity reconsisting the state of the bashty design purb-bursten door handles. Adjustable singli-width hubilconstruction heard-type front seat. Wathable singly headlining. Separa pagagase compartments accessible from uniside of eas. Spare who housed in luggage compartment accessible from uniside of eas. Spare who housed in luggage compartment accessible from uniside of eas.

CONTROCS

Choke, combined ignition-starter switch, lighting switch, instrume
light and windshield wiper. Plastic control knobs. Foot operab
leght and windshield wiper.

Conveniently grouped cluster inmediately in front of efficies included precdometer, fuel gauge, sammeter, oil pressure warning light, direction ndicastor warning lights, ignition warning light, head-lamp main beam ndicastor warning lights, ignition warning light, head-lamp main beam ocis panes.

Two-break ventibleted generateles, compensated voltage control. Dri "V" bein sasily adjustable. Saster motor. Bustlety: 32 volt, 57 as be: at 20 hr. rate.

WHEELS And Panes assets figure, Austless steel hub-cape. Ty
Pressed steel with wide base rims. Rustless steel hub-cape. Ty
6.00.3

STERRING, Ratio 18.0 to 1. Stearing wheel diamete Recirculatory, ball type. Karlo 18.0 to 1. Stearing wheel diamete Trins. Two spoke safety type.

double-acting shock absorbers.

Advanced policional configuration for the configuration of the configura

As the property of the state of

Cluths, development of the president of

COOLING SYSTEM Belt-driven fan and water pump with thermostatic heat control. It and fin type realistor. Capacity of system 32 pints.

phragm type fuel pump mechanically operated. Down drain burettor has special choke control and is fitted with combined anest and silencer. Electrical petrol gauge. Petrol tank as a secity 10.5 gallons.

| 12 volt battery and coll (battery accessibly located under hood) = | 12 volt battery and coll distributor has automatic advance and retard and additional vacuum control. Spatising plug size 14 mm. Firing order 1, 5, 3, 6, 2, 4.

MOITAZISSUZ MOITAZISSUZ MOITAZISSUZ MOITAZISSUZ MOITAZISSUZ MOITAZISSUZ MOITAZISSUZ MOITAZISSUZ PROMITAZIS DE SENTINDA DE SENT

Act collecter studied with the control of the control of the collecter studied with the collecter stud

SPECIFICATIONS ZEPHYR-SIX SEDAN

# Styled and sized for modern living . . .



The Zephyr-Six interior is a combination of modern, graceful styling and spaciousness. With more leg room, more shoulder room, more hip room and more head room there is ample space for six big people.

This comfort-planned interior blends perfectly with Zephyr's sleek, sweeping exterior lines. A luxury note is the centre armrest in the front seat, and the rich vinyl-type upholstery which not only lasts longer but is easier to keep clean.

There's extra safety, too, built into Zephyr... the facia panel is covered with fabric to guard against sun-glare, and the steering wheel is slightly 'dished' to give added protection against impact.


All instruments and controls are grouped around the steering column for easier reading and handling . . . and the ratchet-type hand brake is placed to the left of the steering column, within easy reach of the driver.

A new type of ventilation system has a re-located intake to ensure that only fresh, clean air enters the car. As well as the glove box, there's a convenient roomy parcel tray beneath the facia panel on the passenger seat side, and a parcel shelf stretching full width behind the rear seat. Summed up, Zephyr's interior gives you luxury and bisness' greater than in many far hieher projeed cars.





# Power with modern meaning



This O.H.V. oversquare engine gives Zephyr the greatest power of any car in its class. With an R.A.C. rating of 25.4 h.p., it develops a maximum 80 B.H.P. You'll enjoy smoother cruising speeds, more instant responsiveness and greater fuel economy. The modern "oversquare" principle of its design lessens internal friction. adds to smoothness, increases life.



Zephyr's oversquare type engine wherein the length of the piston stroke is less than the diameter of the cylinder bore results in higher cruising speeds without pistons racing - and consequently less friction and wear, more efficient performance and far longer life.



The Overhead valves permit a more efficient combustion head shape which spreads the explosion evenly, giving more responsive power, smoother running and more efficient and economical use of fuel.



The double Venturi carburettor features a unique new metering system for greater fuel economy than ever before. provides the most efficient fuelair mixtures for the greatest power charges and economy.

## For longer engine life . . .

To lengthen engine life provi-sion is made for a direct injection of oil into the cylinder walls when the engine is started from cold, and larger main and connecting rod bearings are used.

Engine lubrication is by pressure feed by a submerged gear pump to crankshaft m arings, big-end bearings and mshaft bearings.

The added power of 12-volt ignition system that ensures more positive and quicker cold weather starting.

# Travel with modern ease

Zephyr's smoothness of ride and complete driver control result from the very latest suspension system. Rough surfaces are taken with a gentleness, free from pitch or sway, and Zephyr's wide track, low centre of gravity provide unmatched stability of ride safer, easier cornering, and more relaxing driving-ease. And stops are arrow straight when you call on Zephyr's swift-acting brakes . . . they have a total lining area of 147 sq. ins., for smoother, surer braking.



Shorter turning circle. Easier to park. easier to manoeuvre in traffic, simpler to handle in narrow places, Zephyr's driver enjoys the handling ease of a short turning circle of only 36 feet.



You enjoy a smoother ride with centre-slung seating. All seats are suspended 'hammock-wise' between front and rear axles to reduce upward and downward movement of the ride.



The hooded headlamps don't just look smarter, they're safer - the projection providing a hood which eliminates upward glare. The parking lights are flasher type for telling oncoming traffic you are turning.



Latest design tail-light assembly is large, clearly defined. As well as your 'stop' light, amber hand operation. Turning the turn signal lights are incorporated ignition key to the right switches in the unit—another safety feature. on the ignition, and, in the one An inbuilt reflector completes a action, a further turn of the



Yet another extra feature is the key-turn ignition for onesmart three-purpose assembly. key to the right starts the motor.



Centre-fill fuelling. The petrol tank filler cap is centrally located for 'filling up' from either side. It is concealed behind the rear number plate which is hinged and spring-loaded. This position eliminates any risk of the bodywork being scratched by the petrol pump hose.



More than ever before, Zephyr sets the fashion with styling designed to stay modern for years ahead.

Longer and wider than any other car in its class, Zephyr is a full six seater with beautiful, graceful sweeping lines.

The crisp, long-low look . . . with a refreshing absence of clutter . . . demands attention from any angle. Coming toward you the low-set chrome grille emphasises that low, wide appearance, and when showing you fleet 'heels' there's an impression of dash from the flowing, distinctive rear design.

Yes, here is the car that for 'looks' alone sets heads turning . . . but there's much much more than looks that you'll admire. There's also more that's new than ever before in comfort. luxury and performance . . . in short, Zephyr is a skilful blend of all that's new and best in modern motoring and is by far the finest value in its class

Zephyr-Six - a new concept of styling with a big, wide look of action