

# KEPERCAYAAN KELUARGA KEBANGGAAN INDONESIA



Accessories: optional



Jumlah Negara  
Tujuan Ekspor Terbanyak  
2007 - 2008  
**GAIKINDO**  
IIMS 2009

# APV ARENA

## Interior Mewah dan Nyaman

Suzuki APV Arena hadir dengan ruang yang legaa serta fitur yang modern, menjadikan ruang terasa lebih luas, nyaman dan mewah. Dapatkan sebuah kebanggaan penuh kenyamanan dan kemewahan untuk Anda dan keluarga.



Coil Spring yang nyaman dan stabil

Mesin lebih irit dan bertenaga



Ac Double Blower yang modern dan sejuk (GX & SGX)

Captain Seat yang mewah dan luas (SGX)

## colors

(warna sesuai tipe mobil)



Burgundy Red Pearl



Radiant Red Pearl



Graphite Grey Metallic



Purplish Silver Pearl




Diamond Blue



Cool Black Metallic



Silky Silver Metallic



### SPECIFICATION

		GL	GX-MT	GX-AT	SGX-MT	SGX-AT
<b>DIMENSIONS</b>						
Overall length	(mm)			4225		
Overall width	(mm)			1655		
Overall height	(mm)			1855		
Wheelbase	(mm)			2625		
Tread	Front (mm)			1435		
	Rear (mm)			1435		
Minimum ground clearance	(mm)	175 (Diff)		170 (AT oil pan)	175 (Diff)	170 (AT oil pan)
Minimum turning radius	(m)			4.9		
<b>WEIGHTS</b>						
Curb weight	(kg)			1.160-1.325		
Gross vehicle weight	(kg)			1.950		
<b>CAPACITIES</b>						
Seating capacity	(persons)		8			7
Fuel Tank Capacity	(liters)			46		
<b>ENGINES</b>						
Type				G15A		
Number of cylinders				4		
Number of valves				16		
Piston Displacement	(cc)			1.493		
Bore x stroke	(mm)			75.0 x 84.5		
Compression ratio				9.5 : 1		
Maximum output	(PS/rpm)			105/6,000		
Maximum torque	(N.m/rpm)			126/3,000		
Fuel system				Multi Point Injection		
<b>TRANSMISSIONS</b>						
Type		5-speed Manual		4-speed Automatic	5-speed Manual	4-speed Automatic
Gear ratios	1st	4.545		2.826	4.545	2.826
	2nd	2.628		1.493	2.628	1.493
	3rd	1.865		1.000	1.865	1.000
	4th	1.241		0.730	1.241	0.730
	5th	1.000		-	1.000	-
	Reverse	4.431		2.703	4.431	2.703
	Final	4.300		5.375	4.300	5.375
<b>STEERING</b>						
Type				Rack & Pinion		
Power Steering						
<b>SUSPENSIONS</b>						
	Front			Mac Pherson Strut & Coil Springs		
	Rear			3-link rigid axle with coil springs		
<b>BRAKES</b>						
	Front			Ventilated Discs		
	Rear			Leading & Trailing Drums		
<b>TYRES &amp; Wheels</b>						
Tyres (Front & Rear)		185/80 R14		195/65 R15		
Wheels		Alloy 14"		Alloy 15"		
<b>SAFETY AND SECURITY</b>						
Seatbelts 3-point ELR	Front					
	2nd row			With height adjusters		
	3rd row					
Side Impact Beam						
Keyless entry						

Standard and optional equipment availability may vary for individual markets. Please enquire at your dealers, as specifications and illustrations may refer to model is not available in your region. PT SUZUKI INDOMOBIL MOTOR reserves the right to change without prior notice, prices, colors, materials, equipment, specifications and models, also to discontinue models.



Sole Agent:  
PT. SUZUKI INDOMOBIL MOTOR  
Jl. Diponegoro Km. 38.2 Tambun-Bekasi

Sole Distributor:  
PT. SUZUKI INDOMOBIL SALES  
Warna Indomobil 7<sup>th</sup> Floor, Jl. M.T. Haryono Kav.8, Jakarta 13330

www.suzuki.co.id





Way of Life!



APV  
*Luxury*

Jumlah Negara  
Tujuan Ekspor Terbanyak  
2007 - 2008  
GAIKINDO  
IIMS 2009



APV  
GO GLOBAL  
LEBIH DARI  
80 NEGARA  
DI DUNIA

APV  
*Luxury*

Suzuki APV LUXURY hadir bagi Anda yang benar-benar spesial. Eksteriornya tampil lebih **elegan** dan **berkelas**, memadukan kemewahan dan kenyamanan untuk keluarga.

APV LUXURY...Kepercayaan Keluarga, Kebanggaan Indonesia.



## Specification

		SGX-MT	APV	SGX-AT
<b>DIMENSIONS</b>				
Overall length	(mm)		4,225	
Overall width	(mm)		1,655	
Overall height	(mm)		1,855	
Wheelbase	(mm)		2,625	
Tread	Front (mm)		1,435	
	Rear (mm)		1,435	
Minimum ground clearance	(mm)	175 (diff)		170 (AT oil pan)
Minimum turning radius	(m)		4.9	
<b>WEIGHTS</b>				
Curb weight	(kg)		1,160-1,325	
Gross vehicle weight	(kg)		1,950	
<b>CAPACITIES</b>				
Seating capacity	(persons)		7	
Fuel Tank Capacity	(liters)		46	
<b>ENGINES</b>				
Type			G15A	
Number of cylinders			4	
Number of valves			16	
Piston Displacement	(cc)		1,493	
Bore x stroke	(mm)		75,0 x 84,5	
Compression ratio			9.5	
Maximum output	(PS/rpm)		105/6,000	
Maximum torque	(N.m/rpm)		126/3,000	
Fuel system			Multi Point Injection	
<b>TRANSMISSIONS</b>				
Type		5-speed Manual		4-speed Automatic
Gear ratios	1 <sup>st</sup>	4,545		2,826
	2 <sup>nd</sup>	2,628		1,493
	3 <sup>rd</sup>	1,865		1,000
	4 <sup>th</sup>	1,241		0,730
	5 <sup>th</sup>	1,000		-
	Reverse	4,431		2,703
	Final	4,300		5,375
<b>STEERING</b>				
Type		Rack & Pinion (Power Steering)		
<b>SUSPENSIONS</b>				
	Front	Mac Pherson Strut & Coil Springs		
	Rear	3-link rigid axle with coil springs		
<b>BRAKES</b>				
	Front	Ventilated Discs		
	Rear	Leading & Trailing Drums		
<b>TYRES &amp; WHEELS</b>				
Tyres (Front & Rear)		195/65 R15 or 215/50 R17		
Wheels		Alloy 15" or 17"		
<b>SAFETY AND SECURITY</b>				
Seatbelts 3-point ELR	Front	With Height Adjuster		
	2nd row	●		
	3rd row	●		
Side Impact Beam		●		



New Design Front Grille



New Design Front Bumper



New Side Body Panel




New Alloy Wheels Std 15" or 17"



New Design Rear Upper Spoiler



New Design Rear Bumper with Reverse Parking Sensor



New Emblem "Luxury"



New Muffler Extension



Keyless Entry & Alarm

### Colors




Pearl White



Cool Black Metallic

### Dimension



Standard and optional equipment availability may vary for individual markets. Please enquire at your dealers, as specifications and illustrations may refer to models not available in your region. PT. Suzuki Indomobil Motor reserves the right to change, without prior notice, prices, colours, materials, equipment, specifications and models, and also to discontinue models.

www.suzuki.co.id

