VALIANT CET











SPECIFICATIONS

DIMENSIONS

DIMENSIONS
Wheelbase 108°; overall length 192,32°; front track \$8.4°; rear track, \$6.6°; overall height (3 passengers), \$4.5°.
ENGINE
Pacer 225 cubic inch 6-cylinder in line
O.H.V. 30° inclined; bore 3.40°; stroke,
4,125°. Compression ratio 9.2:1. 2-barrel
downdraught carburettor.
TRANSMISSION

TRANSMISSION

All synchro 3-speed manual with floor shift lever. Ratios 1st: 2.95:1; 2nd: 1.69:1; 3rd: 1.00:1; Reverse: 3.80:1.

REAR AXLE
Hypoid, semi-floating, ratio 3.23:1. SureGrip differential available with rear axle
ratios 3.5:1 or 2.92:1 as factory fitted

option. BRAKES

Dual master cylinders with separate front and rear brake circuits. Duo-Servo finned drum. Swept drum area 254.5 sq. ins. Shoe clearance automatically adjusted during reverse stops. Front disc brakes optional. SUSPENSION

Independent front suspension with chromium alloy steel torsion bars and sway bar. Four-

leaf longitudinal rear springs with telescopic shock absorbers. WHEELS & TYRES

Pressed steel 5.5" wide double-sided safety rims. 6.95 x 14" x 4 ply red-line sports tyres standard.

FUEL TANK Capacity 15 gallons. INSTRUMENTATION

Odometer. Tachometer Fuel gauge.

ruet gauge.
Ammeter.
Water temperature gauge.
Oil pressure warning light.
Braking system warning light.
Handbrake warning lights.
Indicator warning lights. High beam warning light. Variable instrument panel light.

WEIGHT 2970 lbs. unladen but with petrol and water

EQUIPMENT

Safety: Front lap and sash seat belts.
Energy absorbing steering column.
Padded steering wheel hub. Dual master cylinder braking system. Power operated windscreen washers. 2-speed windscreen wipers. Non-glare windscreen wiper arms and

blades. Safety padded sunvisors. Swing-away interior rear-view mirror. Full width upper and lower instru-ment panel padding. Recessed instrument panel. Exterior rear-view mirror. Safety flush-fitting door handles.

"Up top, up front' park and turn signal lights.

Side view tail and turn signal lights. Double-sided safety rim wheels. Dual horns.

Safety zone windscreen. Panoramic rear window. New 75-50 watt "big beam" headlights.

Anti-burst door locks. Comfort and Convenience: Reclining tower-back bucket seats with integral headrest. Fingertip horn tabs and half horn ring.
Padded arm rests all doors.
Recessed cigar lighter.
Ash trays front and rear.
Cont. book.

Coat hook. Interior courtesy light. Reversing lights. Remote control hood lock. Fresh flow ventilation. 26½ cubic foot trunk space.

The policy of Chrysler Australia Limited is one of continual improvement in design and manufacture wherever possible to assure a still finer car. Hence specifications, equipment and prices are subject to change without notice.















SPECIFICATIONS

DIMENSIONS
Wheelbase 108"; overall length 192.32"; front track 58.4"; rear track, 56.6"; overall

front track 58.4"; rear track, 56.6"; overall height (3 passengers), 54.5".

ENGINE
Pacer 225 cubic inch 6-cylinder in line
O.H.V. 30° inclined; bore 3.40"; stroke,
4125". Compression ratio 9.2:1. 2-barrel
downdraught carburettor.

TRANSMISSION

All synchro 3-speed manual with floor shift lever. Ratios 1st: 2.95:1; 2nd: 1.69:1; 3rd: 1.00:1; Reverse: 3.80:1.

REAR AXLE

Hypoid, semi-floating, ratio 3.23:1. Sure-Grip differential available with rear axle ratios 3.5:1 or 2.92:1 as factory fitted

option. BRAKES

Dual master cylinders with separate front and rear brake circuits. Duo-Servo finned drum. Swept drum area 254.5 sq. ins. Shoe clearance automatically adjusted during reverse stops. Front disc brakes optional. SUSPENSION

Independent front suspension with chromium alloy steel torsion bars and sway bar. Fourleaf longitudinal rear springs with telescopic shock absorbers.

WHEELS & TYRES

Pressed steel 5.5" wide double-sided safety rims. 6.95 x 14" x 4 ply red-line sports tyres standard.

FUEL TANK Capacity 15 gallons. INSTRUMENTATION

Odometer. Tachometer. Fuel gauge. Ammeter. Water temperature gauge Oil pressure warning light. Braking system warning light. Handbrake warning light. Indicator warning lights. High beam warning light. Variable instrument panel light.

WEIGHT 2970 lbs. unladen but with petrol and

EOUIPMENT

Sarety: Front lap and sash seat belts. Energy absorbing steering column. Padded steering wheel hub. Dual master cylinder braking system. Power operated windscreen washers. 2-speed windscreen wipers. Non-glare windscreen wiper arms and

blades Safety padded sunvisors. Swing-away interior rear-view mirror. Full width upper and lower instru-ment panel padding. Recessed instrument panel.

Exterior rear-view mirror. Safety flush-fitting door handles.

"Up top, up front' park and turn signal lights. Side view tail and turn signal lights.

Double-sided safety rim wheels. Dual horns.

Safety zone windscreen. Panoramic rear window. New 75-50 watt "big beam" head-

Anti-burst door locks. Comfort and Convenience: Reclining tower-back bucket seats with integral headrest. Fingertip horn tabs and half horn ring. Padded arm rests all doors. Recessed cigar lighter.

Ash trays front and rear. Coat hook. Interior courtesy light. Reversing lights.

Remote control hood lock. Fresh flow ventilation. 26½ cubic foot trunk space.

The policy of Chrysler Australia Limited is one of continual improvement in design and manufacture wherever possible to assure a still finer car. Hence specifications, equipment and prices are subject to change without notice.







5 SEATER SPORTS

