

# saloons

The 120Y 2 & 4 door saloons are quality cars, attractively styled with a spacious interior to offer you first class, comfortable motoring at a sensible price.

The front seats recline and all seats are upholstered in luxurious cloth, trimmed with vinvl leatherette. Deep pile fitted carpets add to the refinement of the interior, while comfort for all the occupants is ensured by a really efficient heating and ventilation system.

Concern for the driver is reflected in many aspects of 120Y design.

The instruments are clearly visible and all controls are light to operate. The slick gearchange is a joy to use and an automatic gearbox is available if you prefer the car to do the thinking.

As for performance, the 120Y is brisk and lively with a maximum speed of up to 90 m.p.h., so that motorway cruising at 70 is relaxed and undemanding.

The superior equipment of the 120Y saloon includes a two wave band push-button radio, heated rear window, two-speed wipers with electric washers, tinted glass, reversing lights, hazard flashers and lockable fuel filler cover.

On the 4 door you'll also find radial ply tyres, head restraints and a clock, and both models are available in high gloss metallic colours at extra cost.

# **SPECIFICATIONS**

### **ENGINE:**

4-cylinder in-line OHV, water-cooled. Bore 73.0mm, stroke 70.0mm, capacity 1,171cc. Maximum power 65bhp (DIN) at 6,000rpm. Maximum torque 68 lb.ft. (DIN) at 3,600rpm. Compression ratio 9.0 to 1. Mechanical fuel pump. Twin-choke carburettor.

### TRANSMISSION:

4-speed all-synchromesh gearbox with floor change. Gear ratios: 1st 3.76, 2nd 2.17, 3rd 1.40, Top 1.0, Reverse 3.64. Diaphragmspring clutch, mechanical operation. Hypoid final drive, ratio 3.90 to 1. Top gear 16.0mph per 1,000rpm.

Recirculating-ball type, ratio 16:1, with collapsible energyabsorbing column. Steering lock. Safety-padded two spoke wheel.

### SUSPENSION:

Front, MacPherson struts with coil springs, lower links and anti-roll bar. Rear, live axle with semi-elliptic springs. Telescopic dampers all round.

# BRAKES:

Servo-assisted brakes. Disc front and drum rear with dual circuits. Handbrake between front seats.

### WHEELS AND TYRES:

Pressed steel wheels with 4.5 inch rim. Four stud fixing.

Cross-ply 6.00 — 13 inch tyres.

Radial-ply 155 SR — 13 inch tyres.


### SERVICE AND CAPACITIES

FUEL:	10.4 gallons
Engine oil (sump & filter)	5.8 pints
Gearbox oil	2.1 pints
Axle oil	1.6 pints
Service interval	6,000 miles

## DIMENSIONS WEIGHTS

DIMENSIONS, WEIGHTS.	
Overall length	12ft. 11 ½ in.
Overall width	5ft. 1in.
Wheelbase	7ft. 8in.
Track, front & rear	4ft. 1in.
Kerb weight	1749 lb. (2-door)
	1782 lb. (4-door)

2-door 825 lb., 4-door 792 lb. Maximum payload Maximum towing weight (with trailer braking)







Comprehensive facia of 4-door saloon.



Luxurious interior of 4-door saloon.



Two wave-band push-button radio.



Powerful heater is part of integral ventilation system. Two speed fan boosts hot or cold air as

