

162



BAKER MOTORS (Rochdale) LTD.
249/251 OLDHAM ROAD,
ROCHDALE.

VOLVO 264



The Volvo 264 GLE has plush or leather upholstery dependent on exterior colour chosen. All the interior trim is flame resistant.

The instrumentation includes a comprehensive system of warning and reminder lights.

	264 DL	264 GLE
Engine		
Designation	B27A	B27E
No. of cylinders	6	6
Displacement cm ³	2664	2664
Bore x stroke, mm	88.0 x 73.0	88.0 x 73.0
Max output hp at r/m DIN	125/5250	140/6000
Max output kW at r/s DIN	92/88	103/100
Max torque kpm r/m DIN	20.0/3500	20.8/3000
Max torque Nm at r/s DIN	196/58	204/50
Compression ratio	8.7:1	8.7:1
Carburation	Single	CI injection system
	cross-draught	
Other standard equipment¹⁾		
Headlight wipers/washers	—	Yes
Instrumentation	Clock	Clock, Tachometer
Steering wheel diameter	400 mm	400 mm. Integral foam covered
Electrically powered windows	—	Front and rear side windows
Tinted glazing	—	Yes
Rear window sun blind	—	Yes
Electrically operated outer rear-view mirrors	—	Yes
Make-up mirror	—	In glovebox
Upholstery	Cloth	Plush or leather ²⁾
Full carpeting	Textile, short pile	Textile, deep pile
Electrically heated driving seat	—	Yes
Air conditioning	—	Yes
Stereo loudspeakers	—	Built into front doors
Fixed head restraints	Front seats	Front and rear seats
Oddments storage	In front doors	In front doors and front seat backrests
Luggage compartment trim	Full textile carpeting	Full textile carpeting. Spare wheel cover
Luggage compartment lighting	Yes	Yes
Rims	5J-14"	5.5J-14"
Steel braced radial ply tyres	175SR14	185/70HR14

¹⁾ The equipment items listed in this table are additional to those specified in the text below.

²⁾ Depending on paint finish selected.

Engine
Water-cooled. Overhead camshaft and cross-flow aluminium-alloy cylinder head. Valve system: rocker arms. Fuel requirement: 93 octane.

Cooling system
Sealed and frost-proofed. Capacity 2.4 Imp. galls (10.9 litres).

Electrical system
12V/70Ah battery. 55A alternator.

Transmission
The Volvo 264 DL is available with a four-speed manual gearbox and an electrically-controlled overdrive, or optionally, an automatic transmission. The Volvo 264 GLE has an automatic transmission as standard.

Fuel tank
Safety location beside rear axle. Capacity 13.2 Imp. galls. (60 litres).

Steering gear
Rack and pinion. Safety steering column of telescopic type. Ratios 17.1:1 power-assisted. Number of turns lock to lock 3.5.

Suspension
Front: spring strut type with stabiliser. Rear: live, carried in rubber-mounted control arms and torque rods. Transverse location by track rod. Coil springs and telescopic shock absorbers with stabiliser.

Braking system
Power-assisted, all-disc. Dual circuit, triangle-split system. Each circuit operates simultaneously on both front wheels and one each of the rear wheels. Brake pipes of rust-resistant copper and nickel alloy. On Volvo 264 GLE models, the front discs are specially ventilated. Relief valves in each circuit prevent the rear wheels from locking up prematurely during emergency braking. Master cylinder of stepped-bore type. Handbrake operates on rear wheels through separate drums.

Instrumentation
Housed in padded dashboard. Rheostat-controlled instrument lighting. Six-figure mileometer with tripmeter, fuel gauge and coolant temperature gauge. Warning lamps for charging, oil pressure, main beam, turn indicators, handbrake and brake circuit failure. Bulb integrity sensor. Glovebox lighting. Combined steering and ignition lock. Centre console: controls for electrically heated rear window, rear foglights, four-way hazard warning lights and also for heating and ventilation system. "Fasten seat belts" reminder. Cigar lighter. Ashtray. Space for a radio.

Other standard equipment
Combined stalk for turn indicators, main and dipped beam and headlight flasher. Combined stalk for two-speed windscreen wipers and electric windscreen washers. Rectangular, halogen headlights with separate reflectors for main and dipped beams. Automatic day running lights. Automatic reversing lights. High impact laminated windscreen. Padded sun visors. Day/night rearview mirror of safety type. Roof lining of moulded fibreglass. Sliding steel sunroof. Inertia reel front seat belts. Inertia reel seat belts for two outer rear seats, lap belt in centre. Rear "fasten seat belts" reminder. Driving seat height adjustment by levers. Adjustable lumbar support. Child-proof locks in rear side doors. Impact absorbing bumpers. Mudflaps all round. The Volvo 264 GLE also has rear courtesy light and metallic paint. Towing points front and rear.

Turning circle diameter
Between kerbs 32' 2" (9.8 m)

Weights
Kerb weight, approx. 1350-1390 kg
2974-3062 lb.
Total weight, approx. 1840 kg
4054 lb.
Trailer weight 1500 kg
3307 lb.

Warranty
Twelve-month warranty including labour and parts, irrespective of mileage.

The factory reserves the right to make changes at any time, without notice, to prices, colours, materials, equipment, specifications and models and also to discontinue models.



VOLVO

RSP/PV 4195-77, Engelska/Englanc