CHASSIS CAB





FIRST-IN-CLASS²

HIGH-STRENGTH, MILITARY-GRADE, ALUMINUM ALLOY BODY AND CARGO BOX / INFLATABLE REAR-SEAT OUTBOARD SAFETY BELTS³

BEST-IN-CLASS

40,000 LBS. MAX. GROSS COMBINED WEIGHT RATING (GCWR)⁴

/ 31,900 LBS. MAX. TOWING CAPACITY⁴ / 12,750 LBS. MAX.

PAYLOAD CAPACITY⁴ / 7,500 LBS. MAX. FRONT GROSS AXLE WEIGHT

RATING (GAWR)⁴ / 430 LB.-FT. OF GAS TORQUE / MOST AVAILABLE

CONFIGURATIONS / MOST AVAILABLE CONFIGURATIONS FOR

CNG/PROPANE UPFITS

CLASS EXCLUSIVE

✓ STANDARD FLAT LOAD FLOOR INSIDE⁶

6.8L TRITON® V10 GAS ENGINE / COLLAPSIBLE AND LOCKABLE
UNDER-SEAT STORAGE3.5 THAT FOLDS INTO FLAT LOAD FLOOR
/ PROGRAMMABLE UPFITTER INTERFACE MODULE3 / 110V/400W
POWER OUTLETS IN CAB3 / LED SIDEVIEW MIRROR SPOTLIGHTS3


¹6000-series aluminum alloy. ²Class 3-5 Chassis Cabs based on Ford segmentation. ³Available feature. ⁴When properly configured. See charts on pages 23-24 for maximum ratings by configuration. ⁵Crew Cab only. ⁵SuperCab and Crew Cab.

Vehicles throughout this brochure may be shown with optional and aftermarket upfit equipment, and without standard antenna.

- 1. An Open C-Channel Frame aft of cab features a standard 34" frame-rail width.
- 2. Rugged Driveline Components include stronger and more capable axles than the previous generation. Reengineered with new gear and bearing designs, they're optimized for weight to be more efficient than their predecessors. Plus, driveshafts, transfer cases and U-joints were upgraded to handle the massive torque output of the Super Duty engines. Rear axles on DRW trucks have more weight-carrying and towing capability than the previous generation.
- 3. 95% High-Strength Steel makes up the frame, which is fully boxed under the cab and forward. 8 times stiffer than the previous generation, the frame handles a wide range of upfits, from flat and dump beds to wrecker, service and delivery bodies. Up to 10 crossmembers enhance strength, with some through-welded to increase stiffness.
- 4. A First-in-Class High-Strength, Military-Grade, Aluminum Alloy Cab reduces body weight. Ford engineers reinvested those weight savings into strengthening the frame and driveline components for the incredible capability of Super Duty.



- 5. A Programmable Upfitter Interface Module¹ allows upfitters to properly connect their electrical equipment to the Controller Area Network (CAN) busses or ports. This connection allows for easy integration of upgrades to meet customer needs.
- 6. An Upgraded Front Axle¹ and upgraded front coil springs¹ compared to the previous generation provide a best-in-class available Front Gross Axle Weight Rating (FGAWR) of 7,500 lbs. on Super Duty F-450/F-550 Chassis Cab models enabling them to carry taller utility buckets and cranes, bigger snowplows, and more.
- 7. 4-Channel Brake Controls allow for the addition of AdvanceTrac® with RSC® (Roll Stability Control™)² and trailer sway control² on Chassis Cab DRW models bringing an added measure of stability to the Super Duty fleet on multiple road surfaces.
- 8. Larger Brake Rotors than the previous generation feature a larger brake pad usable volume, increasing both pad and rotor life. They are key components of a completely reengineered brake system, including a larger master cylinder with more volume, which reduces the risk of thermal brake fade under extreme braking conditions.



Aft-of-axle frame extensions¹ allow easy body and vocational equipment upfits. When you're upfitting, flexibility is the name of the game.





6.7L POWER STROKE V8 TURBO DIESEL

750 | 330 LB.-FT. | HORSE TORQUE | POWER

ROBUST HIGH-ALTITUDE PERFORMANCE

comes courtesy of the high airflow supplied by the diesel's variable geometry turbocharger. Tuned specifically for this application, the turbocharger forces air into the cylinders to enhance performance, helping to deliver maximum power quickly.

EXCELLENT THROTTLE RESPONSE is

delivered in part by a high-pressure, common rail fuel injection system. The fuel pump develops up to 29,000 psi operating pressure, and piezo-controlled fuel injectors provide precise injection. This combination yields superior fuel atomization, delivering excellent throttle response.

is maintained by a masterful mix of component materials. Compacted graphite iron (CGI) imparts strength and durability to the deep-skirt engine block, while reducing weight. Cylinder heads made of aluminum help to further reduce weight and feature a 6-head-bolt-percylinder design to help improve sealing and maintain cylinder integrity.

6.2L 2-VALVE GAS V8 FFV

430 385 LB.-FT. HORSE TORQUE POWER

6.8L TRITON 3-VALVE GAS V10

424 | 288 LB.-FT. | HORSE TORQUE | POWER

V8 help ease your heavy-duty workload. A stiff SOHC valvetrain with roller-rocker shafts enables an intake- and exhaust-port layout that optimizes airflow, helping the engine produce gobs of torque down low.

COMBUSTION CYCLE OPTIMIZATION is

achieved through the 6.2L V8 engine's dualequal variable cam timing. It phases the intakeand exhaust-valve opening and closing events simultaneously to optimize low-end torque and peak horsepower. Using 2 spark plugs per cylinder also helps the fuel air mixture burn efficiently, contributing to engine torque.

TIME-TESTED RELIABILITY of the 6.8L V10 gas engine can be attributed to: a deep-skirt engine block and low-friction internal components; electronic throttle control that delivers seamless and consistent engine response; a coil-on-plug ignition system for high-mileage durability, and a 90,000-mile spark plug maintenance interval with regular fluid and filter changes.¹

PROVEN HEAVY-DUTY GAS PERFORMANCE. X2. Your choice of gas engines can power the 2018 Super Duty® Chassis Cab lineup. Designed, engineered, built and torture-tested by Ford, both are paired with our TorqShift® 6-speed automatic transmission. Our Built Ford Tough® 6.8L Triton® V10 engine provides plenty of pull for your heaviest loads. Our E85-capable 6.2L V8, standard on F-350, supplies working power throughout the rpm range to deliver an exceptional combination of driveability, hauling and towing performance. Alternative fuel options for the gas engines include a CNG/Propane Gaseous Engine Prep Package that readies your truck to be upfit for compressed natural gas (CNG), propane autogas, or as a bi-fuel vehicle with the ability to switch between CNG, or propane and gasoline. Providing flexibility and extended range, trucks upfit to a bi-fuel system include a tank for each type of fuel. This may even help you qualify for state incentives related to alternative fuel use, infrastructure or vehicles. Visit www.afdc.energy.gov/afdc/laws for details.2 F-550 XL Regular Cab 4x2. Oxford White. Available equipment. ¹Under normal driving conditions. ²See your Ford Dealer for ordering details.




THE TORQSHIFT TRANSMISSION WITH SELECTSHIFT® capability delivers smooth, efficient performance on the road. SelectShift allows for manual upshift and downshift capability.


Progressive range select mode lets you reduce the available gear range in difficult road/load conditions.

To eliminate unwanted frequent gear-shifting on steep uphill grades, select tow/haul mode, which also allows engine braking to help maintain vehicle speed when descending that grade.


A multi-segment clutch friction-plate design improves oil flow and reduces power loss to help maximize productivity, while a high-efficiency fluid filter has a fluid change interval of 150,000 miles.



- 3-PLATE, 2-STAGE TORQUE CONVERTER handles substantial horsepower and torque forces from the 6.7L Power Stroke® V8 Turbo Diesel, and helps all engines work efficiently at low rpm thanks, in part, to low-speed lockup capability (down to 900 rpm).
- LIVE-DRIVE POWER TAKEOFF PROVISION¹ includes both stationary and mobile modes on diesel and gas.
- 3. SINTER-BRAZED PINION CARRIERS help manage the diesel's extreme low-end torque, as well as the high shift speeds of the gas engines. When teamed with a gasoline engine, the transmission features up to 4-pinion front carriers and 6-pinion rear. Diesel models feature up to 6-pinion carriers in front and up to 8-pinion carriers in the rear.
- SPLIT-SHAFT POWER TAKEOFF capability is standard on diesel models.



F-450 XLT SuperCab 4x4. Oxford White. Available equipment. ¹When properly configured. F-550 Regular Cab DRW 4x2 Diesel with available equipment. See charts on pages 23-24 for maximum ratings by configuration. ²Available feature. ³Driver-assist features are supplemental and do not replace the driver's attention, judgment and need to control the vehicle. ⁴Remember that even advanced technology cannot overcome the laws of physics. It's always possible to lose control of a vehicle due to inappropriate driver input for the conditions. ⁵Trailer brake controller verified to be compatible with electrically actuated drum brakes and certain electric-over-hydraulic brake systems. See your Ford Dealer for details. ⁶F-350 only. ⁵Not including spare tire.



FOR OPTIMAL TOWING PERFORMANCE,

tow/haul mode on the TorqShift® 6-speed SelectShift® automatic transmission helps manage gear selection by keeping the engine in its power band. Lock out upper gears when heavily loaded or when towing on steep grades using the progressive range select mode.

towing, trailer sway control⁴ monitors the motions of the truck to detect trailer sway and

selectively brakes as needed, helping you maintain control of the truck and the trailer. Trailer sway control and hill start assist are standard on both SRW and DRW models. Plus, our integrated trailer brake controller helps balance the performance of the truck and your electric trailer brakes.⁵

TRACK TOWING INFORMATION on the

8" color LCD productivity screen² (sample screens shown at right), such as trailer brake controller settings, vehicle pitch and steering angle, and profiles of up to 10 different trailers – including accumulated miles on each. This is also where you'll be notified by the standard Individual Tire Pressure Monitoring System⁶ if any tire's pressure is low.⁷







MONITOR VITAL VEHICLE FUNCTIONS through the 8" color LCD screen² in the instrument cluster. Choose your favorites (up to 7) and arrange them in the customized MyView menu for greater convenience. Shown above are the Individual Tire Pressure Monitoring System screen, the DEF tank status screen, and the off-road status screen.

SYNC3

STAY CONNECTED ON THE MOVE.

Imagine controlling calls, music and more with just a touch and your voice. SYNC® 3^{1,2} lets you keep your hands on the wheel while it quickly responds to your spoken requests. Or use the responsive touchscreen in the center of your instrument panel to access its many helpful features. Bring the power of Siri® into Super Duty® Chassis Cab with Siri Eyes Free and your paired iPhone® The system also features 2 smart-charging USB ports to help keep your devices powered up and ready to go.

XLT Crew Cab 4x4. Cloth-trimmed interior in Medium Earth Gray. Available equipment.

¹Don't drive while distracted. Use voice-operated systems when possible; don't use handheld devices while driving. Some features may be locked out while the vehicle is in gear. Not all features are compatible with all phones. ²Available feature. ³Available via download and compatible with select smartphone platforms. Learn more at fordpass.com. Message and data rates may apply. ⁴Requires phone with active data service and compatible software. SYNC does not control 3rd-party products while in use. 3rd parties are solely responsible for their respective functionality. ⁵Commands may vary by phone and AppLink software. ⁵Certain restrictions, 3rd-party terms, or message and data rates may apply. See footnote 4 on page 18 and your Ford Dealer for details.



XL





XLT





LARIAT





MODELS

F-350

- Maximum Capabilities¹

5th-Wheel Towing: 24,500 lbs.

Conventional Towing: 17,500 lbs.

Payload: 7,940 lbs.

GCWR: 32,000 lbs.

GVWR: 14,000 lbs.

Front GAWR: 5,250 lbs. (4x2); 6,000 lbs. (4x4)

Equipment Configurations

Engines: 6.2L Gas V8 Flex Fuel E85-capable 6.7L Power Stroke® V8 Turbo Diesel B20-capable

Drivelines: 4x2 or 4x4 · Single Rear Wheel or Dual Rear Wheel

Bodies: Regular Cab, SuperCab, Crew Cab

Trim Series: XL, XLT, LARIAT

F-450

Maximum Capabilities1

5th-Wheel Towing: 26,400 lbs.

Conventional Towing: 17,500 lbs.

Payload: 9,850 lbs.

GCWR: 34,500 lbs.

GVWR: 16,500 lbs.

Front GAWR: 7.500 lbs.

Equipment Configurations

Engines: 6.8L Triton® Gas V10

6.7L Power Stroke V8 Turbo Diesel B20-capable

Drivelines: 4x2 or 4x4 · Dual Rear Wheel only

Bodies: Regular Cab, SuperCab, Crew Cab

Trim Series: XL, XLT, LARIAT

F-550

Maximum Capabilities¹

5th-Wheel Towing: 31,900 lbs.

Conventional Towing: 18,500 lbs.

Payload: 12,750 lbs.

GCWR: 40,000 lbs.

CTTT. 40,000 ibs.

GVWR: 19,500 lbs.

Front GAWR: 7,500 lbs.

Equipment Configurations

Engines: 6.8L Triton Gas V10

6.7L Power Stroke V8 Turbo Diesel B20-capable

Drivelines: 4x2 or 4x4 · Dual Rear Wheel only

Directines. 4x2 of 4x4 Dual Medi Wilder of

Bodies: Regular Cab, SuperCab, Crew Cab

Trim Series: XL, XLT, LARIAT

FRAMES

Number of Crossmembers

7 (145.3" WB); 8 (167.9" WB, 169.3" WB, 179.8" WB); 9 (191.9" WB, 193.3" WB, 203.8" WB); 10 (205.3" WB)

Section Modulus²

12.7 cu. in.

Frame Rail Yield Strength

50,000 psi

Max. Side Rail Section³ (height x width x thickness)

7.50" x 2.74" x 0.28" (F-350)

7.50" x 2.74" x 0.32" (F-450/F-550 145.3" WB, 169.3" WB, 167.9" WB, 179.8" WB and 203.8" WB)

7.50" x 2.74" x 0.60" (F-450/F-550 169.3" WB, 191.9" WB, 193.3" WB and 205.3" WB; F-550 with the Payload Plus Upgrade Package)

MECHANICAL

Front Suspension

Axle (max. rating@ground) - 5,250 lbs. (F-350 4x4);

Charleston 1 201 control

7,000 lbs. (F-450/F-550)

Shock absorbers - 1.38" gas type

Rear Suspension

Axle (max. rating @ ground) -

7,230 lbs. (F-350 SRW); 10,040 lbs. (F-350 DRW);

13,660 lbs. (F-450); 13,660 lbs. (F-550)

Shock absorbers - 1.38" gas type

Brakes

Rotor diameter (front/rear) -

14.29"/14.29" (F-350); 15.39"/15.74" (F-450/F-550)

Lining area (sq. in.; front/rear) -

50.9/39.6 (F-350); 68.8/64.8 (F-450/F-550)

wneels

Number of studs - 8 (F-350); 10 (F-450/F-550)

Bolt-circle diameter -

6.69" (F-350 SRW); 7.87" (F-350 DRW); 8.85" (F-450/F-550)

POWERTRAINS

	6.7L Power Stroke V8 Turbo Diesel	6.2L 2-Valve Gas V8 FFV	6.8L Triton 3-Valve Gas V10
Configuration	OHV (32-valve)	SOHC	SOHC
Fuel injection	High-pressure common-rail	Sequential electronic	Sequential electronic
Induction system	Single-sequential turbocharger; charged air cooler	Specially tuned	Specially tuned
Cooling system	Pressurized series flow	Pressurized series flow	Pressurized series flow
Block material	Compacted graphite iron	Castiron	Cast iron
Valve operation	Push rod/rocker arms	Roller-rocker shafts	Hydraulic roller
Camshaft drive	Gear	Silent chain	Silent chain
Bore/stroke	3.90"/4.25"	4.02"/3.74"	3.55"/4.17"
Compression ratio	16.2:1	9.8:1	9.2:1
Horsepower@rpm	330@2,600	385 @ 5,7504	288@4,0004
Torque lbft. @ rpm	750@2,000	430@3,800	424@3,000
Recommended fuel	Ultra-low-sulfur diesel or B20 (containing 20% or less biodiesel)	Regular unleaded or E85	Regular unleaded
Transmission	TorqShift® 6-speed SelectShift® automatic with tow/haul mode	TorqShift 6-speed SelectShift automatic with tow/haul mode	TorqShift 6-speed SelectShift automatic with tow/haul mode
Standard availability	F-450/F-550: LARIAT	F-350: XL, XLT, LARIAT	F-450/F-550: XL, XLT
Optional availability	F-350: XL, XLT, LARIAT F-450/F-550: XL, XLT		

¹When properly configured. ²Cross-sectional modulus calculated at back of cab. ³Measured to inside of metal. 4Certified to SAE J1349.



STANDARD FEATURES

Mechanical

Axle - Front, narrow-track, Twin-I-Beam (F-350 4x2)

Axle - Front, wide-track, monobeam (F-450/F-550)

Front and rear stabilizer bars

Hydraulic power-assisted steering

Manual locking hubs (4x4)

Stationary Elevated Idle Control (SEIC)1

Suspension - Heavy-duty gas shock absorbers

Suspension - Rear, auxiliary springs

Trailer wiring - 7-wire harness with relays, blunt cut and labeled

Driver-Assist Technology

Autolamp automatic on/off headlamps with rainlamp

Interior

12V powerpoints (2 in instrument panel)

Cabin air filter

Driver and front-passenger grab handles, and rear-passenger

Illuminated and lockable glove boxes (2)

Manual-tilt/-telescoping steering column

Outside temperature display

Overhead console with dual storage bins

Upfitter switches located in overhead console (four 25-amp and

Exterior

Configurable daytime running lamps

Doors - 2 (Regular Cab)

Doors - 4 (SuperCab/Crew Cab)

Front fender vents

Front license plate bracket

Front splash guards (F-450/F-550)

Quad-beam jewel-effect halogen headlamps

Underhood service lamp

Variable-intermittent windshield wipers with washers

Safety & Security

side airbags²

Front-passenger airbag deactivation switch (Regular Cab and SuperCab)

Safety Canopy® System with side-curtain airbags2 and rollover sensor

AdvanceTrac® with RSC® (Roll Stability Control™)

(Regular Cab front-passenger, and all rear-seat positions)

Individual Tire Pressure Monitoring System

SOS Post-Crash Alert System™

Alternator - 200-amp extra-heavy-duty³ (6.2L gas engine)

Alternator - 220-amp extra-heavy-duty³ (diesel engine)

(F-350 DRW gas engine and F-450/F-550 diesel engine)

Battery - 650-CCA, 72-amp-hr, single (6.2L gas engine)

(F-450/F-550 gas engine; F-550 diesel engine)

S S Battery - 750-CCA, 78-amp-hr, single³ (6.2L gas engine)

S S Battery - 750-CCA, 78-amp-hr, single³ (6.8L gas engine)

Engine idle shutdown - 5-minute (diesel engine)

Engine idle shutdown - 10-minute (diesel engine)

Engine idle shutdown - 15-minute (diesel engine)

Engine idle shutdown - 20-minute (diesel engine)

Fuel tank - Dual diesel3 with 40-gallon aft-of-axle and

26.5-gallon mid-ship tanks (DRW diesel engine)

(F-450/F-550 145" and 169" wheelbases)

(standard on F-350 SRW with 17" wheels)

S S Battery - 750-CCA, 78-amp-hr, dual (diesel engine)

0 0 Axle - Rear, 4.30 electronic-locking (SRW gas engine)

Alternator – 240-amp heavy-duty³ (6.8L gas engine)

0 0 S Alternator - 240-amp extra-extra-heavy-duty3

S S S Axle - Rear, 3.73 non-limited-slip (F-350)

(F-450/F-550 diesel engine)

(F-450/F-550 gas engine)

Axle - Rear, 4.88 non-limited-slip

0 0 Axle - Rear, 3.73 electronic-locking (SRW)

0 0 0 Battery - 750-CCA, 78-amp-hr, dual

Frame extension - Aft-axle

S/o S/o S/o Fuel tank - 26.5-gallon mid-ship3

S S Fuel tank - 40-gallon aft-of-axle3

S S S Drivetrain - 4x2

0 0 0 Drivetrain - 4x4

(F-350 with 6.2L gas engine)

0 0 Engine block heater (standard where required)

0 0 Axle - Rear, 4.10 limited-slip (DRW diesel engine)

0 0 S Alternator - Dual, 332-amp total3 (diesel engine)

0 0 0 Alternator - Dual extra-heavy-duty, 377-amp total3

Mechanical

(6.2L gas engine)

(diesel engine)

S S S Axle - Rear, 4.10 non-limited-slip

0 0 Axle - Rear, 4.30 limited-slip³

0 0 Axle - Rear, 4.88 limited-slip3

BUILD YOUR SUPER DUTY® WI CHASSIS CAB | S:Standard 0:Optional P:Package Content

0 0 Jack - 2-ton mechanical (SRW)

0 0

0 0

0 5

side manual lumbar

AL	XLT	LARIAT		XL	XLT	LARIAT		XL	XLT	LARIAT	
)	0	0	Jack - 2-ton mechanical (SRW)		S	F	Cloth 40/20/40 split front seat, center under-seat	0	0	S	110V/400V
)	0	0	Jack – 4-ton hydraulic (F-350 DRW)	-11	ľ		lockable storage with 12V powerpoint, 2-way manual seat		1	-	includes 1
)	0000	0	Jack - 6-ton hydraulic (F-450/F-550)	-10			adjust, driver's side manual lumbar, and folding armrest				if equipped
)	0		Operator-commanded exhaust filter regeneration with	- 14			with cupholders and storage	P	-	S	Accessory
	0	0	active regeneration inhibit (diesel engine)		0		Cloth front bucket seats with 8-way power driver seat, 2-way manual passenger seat, driver's side manual lumbar,	P	S	S	Cruise cont (optional or
1	U	U	Power takeoff (PTO) provision with transmission-mounted live-drive with mobile and stationary modes; includes split-	- 10			and flow-through center console with lockable storage and 2 rear-facing powerpoints ³ (SuperCab/Crew Cab)		П	S	Door trim -
ı			shaft capability with diesel engine only3 (PTO port located			S	Leather-trimmed heated and cooled 10-way power front			S	Dual-zone e
ı			on driver's side; split-shaft capability included with diesel				bucket seats and flow-through center console with lockable	S	0	0	Flooring - B
ı			engine only; torque output is 250 lbft. for diesel and up to 250 lbft. for gas)				storage and 2 rear-facing powerpoints		S	S	Flooring - C
)	0	0	Programmable Upfitter Interface Module			0	Leather-trimmed heated and cooled 10-way power		0	0	Flooring - F
)	-	0	Spare wheel, tire and hydraulic jack (excludes carrier)	- 10			40/20/40 split front seat, center under-seat lockable storage with 12V powerpoint, and folding armrest with	S	S		Mirror - Day
1	0		Speed limitation – 65-mph governed top speed (Fleet only)				cuphoiders and storage			S	Mirror - Aut
)	0		Speed limitation – 75-mph governed top speed (Fleet only)	S	Г		Heavy-duty vinyl 60/40 split flip-up rear seat		P	S	Power-adju
)	-	S	Trailer brake controller with Smart Trailer Tow Connector ³	0	S		Cloth 60/40 split flip-up rear seat	727		75	(SuperCab,
3	S		Transfer case - Manual ³ (4x4)		Г	S	Premium vinyl 60/40 split flip-up rear seat (SuperCab)	P	S	-	Power door
)	0	S	Transfer case - Electronic shift-on-the-fly (ESOF) ³ (4x4)		Г	S	Leather-trimmed 60/40 split flip-up rear seat (Crew Cab)	0	0	0	Rapid-heat
			Driver-Assist Technology		S	S	Rear under-seat fold-flat storage, lockable and partitionable, with 12V powerpoint (Crew Cab)	S	S		(diesel eng Steering wh
)	S		SYNC® Voice Recognition Communications and Entertainment	- 19	S	S	Rear under-seat storage with 12V powerpoint (SuperCab)		L	S	Steering wh
			System with 4.2" color LCD screen in center stack,		Ħ	S	Fold-down rear-seat center armrest with dual integrated		0	0	Vehicle Safe
	0	c	911 Assist,® AppLink® and 1 smart-charging USB port ³				cupholders (Crew Cab)	S			Visors - Adj with mirror
	U	2	SYNC 3 with 8" color LCD capacitive touchscreen in center stack, 911 Assist, AppLink, Apple CarPlay™ compatibility,			0	Heated rear outboard seats ³ (Crew Cab)		S		Visors - Adj
			Android Auto™ compatibility, and 2 smart-charging USB ports ³				Interior		3		with covere
			Seating	S	L		AM/FM stereo with 4 speakers (Regular Cab)		Н	S	Visors - Adj with covere
3			2-way adjustable driver and right-front-passenger	S	L		AM/FM stereo with 6 speakers (SuperCab/Crew Cab)	S	S		Window - R
4	-		head restraints	P	S		AM/FM stereo/single-CD player with MP3 capability	0	0		Window - R
	S	S	4-way adjustable driver and right-front-passenger head restraints	P	S		and 4 speakers (Regular Cab) AM/FM stereo/single-CD player with MP3 capability	0	-	S	Window - R
S			Heavy-duty vinyl 40/20/40 split front seat with 2-way	100			and 6 speakers (SuperCab/Crew Cab)				glass ³ (Sup
			manual seat adjust, driver's side manual lumbar, and			S	Audio System from Sony® with AM/FM stereo/	S	-		Windows -
ļ			folding armrest with cupholders and storage				single-CD player with MP3 capability, 10 speakers and HD Radio™ Technology	P	S	S	Windows -
)			Cloth 40/20/40 split front seat with 2-way manual seat adjust, driver's side manual lumbar, and folding armrest with cupholders and storage	0	S	S	SiriusXM® Satellite Radio³ with 6-month trial subscription⁴ (adds 1 speaker on XLT only)				¹ Final-stag
)			Heavy-duty vinyl front bucket seats with mini-console and driver's side manual lumbar (Regular Cab)		0	0	Voice-activated Navigation System ³ with integrated SiriusXM Traffic and Travel Link® with 5-year subscription ⁴				switches. airbag war apply. See
,			Cloth front bucket seats with mini-console and driver's	S	-		2.3" productivity screen in instrument cluster				ends, Siri
1			cide manual lumbar	2	-		2.3 productivity screen in instrument cluster				a subscrip

S 4.2" LCD productivity screen in instrument cluster³

S 8" configurable color LCD productivity screen

in instrument cluster

W power outlet, 1 in instrument panel; also 1 rear-facing on the flow-through center console, delay for power features

ntrol with steering wheel-mounted controls

on XL for Fleet only) - Sandalwood film appliqués

electronic automatic temperature control

Black vinyl/carpet delete

Carpet with front and rear carpeted floor mats Floor liners3 (SuperCab/Crew Cab)

ay/night rearview uto-dimming rearview

ustable pedals

b/Crew Cab; optional on XLT for Fleet only)

or locks with autolock/unlock at supplemental cab heater3

igine; standard where required) wheel - Black urethane wheel - Color-coordinated leather-wrapped

afe by Console Vault3,5 djustable driver with pocket and front-passenger

djustable driver and front-passenger

red mirrors djustable driver and front-passenger

red and illuminated vanity mirrors Rear, fixed

Rear, fixed with defroster and privacy glass Rear, power-sliding with defroster and privacy perCab/Crew Cab)

Manual

Power with front one-touch-up/-down feature

age manufacturer must supply control

. ²Always wear your safety belt and follow aming label instructions. 3Restrictions may ee your dealer for details. 4After your trial period riusXM audio and data services each require iption sold separately, or as a package, by Sirius XM Radio Inc. See Sirius XM Customer Agreement for complete terms at www.siriusxm.com. All fees and programming subject to change. Trial subscriptions not available in AK and HI. 5Ford Licensed Accessory.

Axle - Front, narrow-track, monobeam (F-350 4x4)

Oil monitor - Intelligent Oil-Life Monitor® (diesel engine)

Oil monitor - Oil-life minder (gas engines)

Power 4-wheel disc brakes with Anti-Lock Brake System (ABS)

Steering damper

Suspension - Front, coil springs

Trailer sway control

Hill start assist

Air conditioning

Coat hooks

Dash-top tray

on Crew Cab

Lighting - Dome light

Lighting - Dual map lights

(front on Regular Cab/SuperCab; front and rear on Crew Cab)

two 40-amp; 40-amp are hot-at-all-times capable)

Front tow hooks (2)

Lighting - 3-blink lane change signal

Lighting - LED roof marker/clearance lamps

Airbags - Driver and right-front-passenger front and front-seat

Belt-Minder® front safety belt reminder

Child-safety-seat top tether anchors

Front height-adjustable shoulder safety belts

(F-350, excludes available spare)

17

ALI	TARIAT	XL XLT LARIAT		XL	XLT	LARIA	# 3	XL	XLT	
0 0	Exterior O Black platform running boards	0 0	Non-configurable daytime running lamps (replaces standard configurable daytime running lamps; Fleet only)	0		Trailer Tow Package ² : aftermarket trailer brake wiring kit (trailer brake controller not included)	0.0	0	0 0	Low Deflection Package ² (F-450/F-550): 2" spacer block (recommended for rear-biased loading)
0 0	Bumper - Black-painted steel	0 0 0	Rear View Camera and Prep Kit (includes loose camera, wiring	0	0	Ambulance Prep Package (Fleet only; requires diesel	2.9	0	0 0	Payload Plus Upgrade Package ² (F-550 145" WB gas engine): upgraded frame, upgraded rear axle, low-
SS	S Bumper - Chrome	0 0 0	bundle, and rearview mirror or center stack video display ²)		Н	engine): dual extra-heavy-duty alternators, 7,000-lb. max. front springs/GAWR rating for configuration selected,				deflection/high-capacity rear springs, 14,706-lb. max.
S	Door handles - Black		Remote Start System ²		operator-commanded exhaust filter regeneration, and	ш			rear GAWR, and 19,500-lb. GVWR	
S	S Door handles - Body-color	200 200	SecuriCode™ keyless entry keypad Skid plate for transfer case (SuperCab/Crew Cab 4x4)		Ш	wide-track axle (F-350 DRW)	0.10	0	0 0	Snow Plow Prep Package ² : computer-selected front
0 0	O Exterior backup alarm by ECCO®1	553		0	0	Ambulance Prep Package with EPA Special Emissions	11.3	ш		springs for snowplow application, and dual alternator
S	S Foglamps	0000	Splash guards - Front (F-350) Wheel-well liners, front			(Fleet only; requires diesel engine): dual extra-heavy-duty alternators, 7,000-lb. max. front springs/GAWR rating for	E	0		(332-amp total)
0 0	O Ford Telematics™ powered by Telogis®¹ – Fleet-tracking system (includes 1 year of service)	0 0 0	Safety & Security			configuration selected, operator-commanded exhaust filter regeneration, wide-track axle (F-350 DRW), and	Ш			XL Decor Group (Fleet only): bright center cap on wheels (SRW only), and chrome bumper
	Glass - Solar-tint	005	Advanced Security Pack with inclination/intrusion sensors ²		Н	federal emissions		0		XL Value Package: 4.2" center stack screen, AM/FM stere single-CD player with MP3 capability, cruise control, brig
SS	S Glass – Privacy-tint on rear doors and rear window; solar-tint on windshield and front doors ²	0	Airbags – Front-seat side and side-curtain airbag delete ² (Fleet only)	0	0 0 Fire/Rescue Prep Package with EPA Special Emissions (Fleet only; requires diesel engine): dual extra-heavy-duty		12		0	center cap on wheels (SRW only), and chrome bumper
	Grille - Black	0	Airbags – Right-front-passenger front, front-seat side	- 10	Н	alternators, 7,000-lb. max. front springs/GAWR rating for	112	ш	0	XLT Value Package: power-adjustable pedals (SuperCat Crew Cab), 8-way power driver's seat (SuperCab/Crew Ca
S	Grille - Chrome 2-bar insert with Carbon Black surround		and side-curtain airbags delete ² (Fleet only)		Н	configuration selected, operator-commanded exhaust filter regeneration, and federal emissions	ш			and SecuriCode keyless entry keypad
5	S Grille - Chrome 2-bar insert with chrome surround	0 0 0	Individual Tire Pressure Monitoring System delete	0	0	Payload Upgrade Package ² (F-550 145" WB gas engine):	H		0	LARIAT Value Package: easy-entry/-exit driver's seat wi
0 0	O Hood deflector, black molded		(F-350 SRW; Fleet only)			upgraded frame, upgraded rear axle, and 19,000-lb. GVWR	16			memory, power-adjustable pedals with memory, PowerSc
0 0	Lighting – Amber LED warning strobes with CHMSL light bar and 2 hood-mounted lights by SoundOff Signal®1.2	0 0 0	Inflatable rear safety belts in outboard seating positions ² (Crew Cab)	100	200	0 16,000-lb. GVWR Package ² (F-450)	П	П		trailer tow mirrors with memory, and Remote Start Syste
0 0	O Lighting - Amber/white LED warning strobes with CHMSL	100	MyKey® technology to help encourage responsible driving	0	0	6.2L CNG/Propane Gaseous Engine Prep Package: hardened engine intake valves and valve seats,	ш	П		
25	light bar and 2 hood-mounted lights by SoundOff Signal 1.2		Perimeter alarm			and bi-fuel manifold		ш		
	O Lighting - Center high-mounted stop lamp (CHMSL) ²	PSS	Remote Keyless Entry System with 2 integrated keyhead transmitter remotes	0	0		ш	ш		
0 5	S Lighting – Utility Lighting System (LED sideview mirror spotlights) ²	PSS	SecuriLock® Passive Anti-Theft System	0		hardened engine intake valves and valve seats	H	ш		
S	Mirrors - Black sideview mirror caps			0	0	Heavy-Service Front Suspension Package ² : front springs upgrade (unless maximum springs have been computer-	1 2	ш		
9	S Mirrors - Body-color sideview mirror caps		Packages	1		selected as included equipment)	ш	ш		
	Mirrors - Manually telescoping trailer tow with 2-way fold	s/ ₀ 0 0	Payload Downgrade Package ² : 9,800-lb. GVWR (F-350 SRW 17" wheels), 10,000-lb. GVWR (F-350 SRW 18" wheels),	0	0	0 0 Extra-Heavy-Service Front Suspension Package ² : front		ш		
	and manual glass		15,000-lb. GVWR (F-450), 17,500-lb. GVWR (F-550)	-10	springs upgrade (unless maximum springs have beer		1111	ш		
S	Mirrors – Manually telescoping trailer tow with 2-way fold, power/heated glass, heated manual spotter mirrors, and integrated clearance lamps and turn signal indicators	0	Power Equipment Group: accessory delay for power features; manually telescoping trailer tow mirrors with 2-way fold, power/heated glass, heated manual spotter mirrors, and			computer-selected as included equipment) 0 Extra-Heavy-Duty Front-End Suspension Package ² (F-450/F-550): upgraded front axle, and 7,500-lb. front				
0 5	S Mirrors – PowerScope® power-telescoping/-folding trailer tow with power/heated glass, heated manual spotter mirrors, integrated clearance lamps, turn signal indicators, high-intensity LED security approach lamps, Utility Lighting System, and driver's side auto-dimming feature		integrated clearance lamps and turn signal indicators; perimeter alarm; power locks with autolock/unlock; MyKey®; power windows with front one-touch-up/-down feature; and Remote Keyless Entry System with 2 integrated keyhead transmitter remotes			springs/GAWR rating High-Capacity Trailer Tow Package ² (F-450/F-550 diesel engine): trailer brake wiring kit, upgraded rear axle, and increased GCWR of 35,000 lbs. on F-450 and 40,000 lbs. on F-550				¹ Ford Licensed Accessory. ² Restrictions may apply. See y dealer for details. ³ Available feature. ⁴ Driver-assist feature are supplemental and do not replace the driver's attention



A Programmable Upfitter Interface Module³ helps upfitters quickly connect their electrical equipment to that of the truck, allowing convenient integration of upgrades to better meet customer needs.

The Rear View Camera and Prep Kit^{3,4} helps make backing up easy. Place the remote-mounted camera wherever you need it, thanks to a wiring harness extension. Then, while slowly backing up, see what's behind you through a video display in the cab.

Up to 6 power sources, including 12V powerpoints³ and 110V power outlets,³ help you recharge your equipment easily. And the combined max. output of these outlets is 400W in Park and 300W when driving.

6 auxiliary upfitter switches are mounted overhead, within easy reach of front-seat occupants.

EXTERIORS/INTERIORS

	XL	XLT	LARIAT
White Platinum Metallic Tri-coat ¹			5 6
Oxford White	1 2	3 4	5 6
Ingot Silver ²	1 2	3 4	5 6
White Gold ²		4	5 6
Stone Gray ²		3 4	5 6
Magma Red ²		4	5 6
Race Red	1 2	3.4	5 6
Ruby Red Metallic Tinted Clearcoat ¹		3 4	5 6
Blue Jeans ²	1 2	3 4	5 6
Magnetic ²	1 2	3	6
Shadow Black	1 2	3 4	5 6






Pairing advanced technology with comfortable, durable materials, the Super Duty® Chassis Cab interior - Regular Cab, SuperCab and Crew Cab - works as hard as you do. To keep you productive all day long, smart storage is everywhere. Even under the rear seat. On Crew Cab models, deployable under-seat storage³ raises up from the floor to form a large bin that can be locked when the seat is down. When not needed, it folds back into the floor to form a convenient flat load floor. And the deep front center console³ is large enough for small tools or hanging file folders.

Regular Cab

Available: XL, XLT




Available: XL, XLT, LARIAT



Crew Cab

Available: XL, XLT, LARIAT



40/20/40 split front seat

Standard: XL, XLT Optional: LARIAT



40/mini-console/ 40 front bucket seats

Optional: XL



40/console/40 front bucket seats

Standard: LARIAT





	Regular Cab F-350 SRW 4x2/4x4	F-350 DRW ¹ 4x2/4x4	F-350 DRW ¹ 4x2/4x4	F-450 DRW 4x2/4x4	F-450 DRW 4x2/4x4	F-450 DRW 4x2/4x4	F-450 DRW 4x2/4x4	F-550 DRW 4x2/4x4	F-550 DRW 4x2/4x4	F-550 DRW 4x2/4x4	F-550 DRW 4x2/4x4
Wheelbase	145.3"	145.3"	169.3"	145.3"	169.3"	193.3"	205.3"	145.3"	169.3"	193.3"	205.3"
Cab-to-axle	60"	60"	84"	60"	84"	108"	120"	60"	84"	108"	120"
Exterior Height Top of cab to ground Top of frame to ground Width Between frame rails Axle clearance Front track Rear tire outside width Overall length	77.9"/81.0"	78.1"/81.0"	78.0"/80.9"	81.7"/81.5"	81.5"/81.3"	81.5"/81.4"	81.3"	81.7"/81.5"	81.7"/81.5"	81.7"/81.6"	81.5"
	32.2"/34.3"	32.3"/34.2"	32.0"/33.8"	35.0"/35.1"	34.5"/34.6"	34.4"	34.4"	35.0"/35.1"	34.4"/34.5"	34.3"	34.3"
	34.1"	34.1"	34.1"	34.2"	34.2"	34.2"	34.2"	34.2"	34.2"	34.2"	34.2"
	8.6"/8.5"	7.9"/7.8"	7.9"	8.2"	8.3"	8.3"	8.3"	8.2"	8.3"	8.3"	8.3"
	68.3"	69.1"	69.1"	74.8"	74.8"	74.8"	74.8"	74.8"	74.8"	74.8"	74.8"
	79.6"	92.2"	92.2"	93.9"	93.9"	93.9"	93.9"	93.9"	93.9"	93.9"	93.9"
	230.7"	230.7"	254.8"	230.7"	254.8"	278.8"	290.7"	230.7"	254.8"	278.8"	290.7"
Weights (lbs.) Max. GVWR ² Max. payload ²	11,100/11,500 4,870/4,860	14,000 7,940/7,550	14,000 7,330/6,930	16,500 9,850/9,540	16,500 9,790/9,450	16,500 9,610/9,300	16,500 9,550/9,230	19,000 12,310/12,000	19,500 12,750/12,410	19,500 12,570/12,260	19,500 12,510/12,190

	SuperCab						Crew Cab					
	F-350	F-350	F-450	F-450	F-550	F-550	F-350	F-350	F-450	F-450	F-550	F-550
	SRW	DRW ¹	DRW	DRW	DRW	DRW	SRW	DRW ¹	DRW	DRW	DRW	DRW
	4x2/4x4	4x2/4x4	4x2/4x4	4x2/4x4	4x2/4x4	4x2/4x4	4x2/4x4	4x2/4x4	4x2/4x4	4x2/4x4	4x2/4x4	4x2/4x4
Wheelbase	167.9"	167.9"	167.9"	191.9"	167.9"	191.9"	179.8"	179.8"	179.8"	203.8"	179.8"	203.8"
Cab-to-axle	60"	60"	60"	84"	60"	84"	60"	60"	60"	84"	60"	84"
Exterior Height Top of cab to ground Top of frame to ground Width Between frame rails Axle clearance Front track Rear tire outside width Overall length	78.3"/81.0"	78.5"/81.2"	81.8"	81.8"/81.6"	82.0"/81.8"	81.8"	78.4"/81.2"	78.6"/81.2"	81.9"/81.8"	81.7"/81.8"	81.9"/81.8"	81.9"/81.7"
	31.9"/33.8"	32.0"/33.7"	34.6"/34.3"	34.6"/34.4"	34.5"/34.3"	34.6"/34.3"	31.7"/33.5"	31.9"/33.7"	34.4"/34.3"	34.5"/34.3"	34.4"/34.3"	34.4"/34.3"
	34.1"	34.1"	34.2"	34.2"	34.2"	34.2"	34.1"	34.1"	34.2"	34.2"	34.2"	34.2"
	8.6"	7.9"/7.8"	8.3"	8.2"	8.3"	8.2"	8.6"	7.8"	8.2"	8.2"	8.2"	8.2"
	68.3"	69.1"	74.8"	74.8"	74.8"	74.8"	68.3"	69.1"	74.8"	74.8"	74.8"	74.8"
	79.6"	92.2"	93.9"	93.9"	93.9"	93.9"	79.6"	92.2"	93.9"	93.9"	93.9"	93.9"
	253.3"	253.3"	253.3"	277.4"	253.3"	277.4"	265.2"	265.2"	265.2"	289.2"	265.2"	289.2"
Weights (lbs.) Max. GVWR ² Max. payload ²	11,500 4,970/4,940	14,000 7,600/7,200	16,500 9,550/9,190	16,500 9,360/9,030	19,500 12,510/12,150	19,500 12,320/11,990	11,500 4,830/4,820	14,000 7,460/7,040	16,500 9,380/9,070	16,500 9,230/8,940	19,500 12,340/12,030	19,500 12,190/11,900

Interior (front/rear)	Regular Cab	SuperCab	Crew Cab
Head room	40.8"/ -	40.8"/40.3"	40.8"/40.4"
Leg room (max.)	43.9"/ -	43.9"/33.5"	43.9"/43.6"
Hip room	62.5"/ -	62.5"/64.7"	62.5"/64.7"
Shoulder room	66.7"/ -	66.7"/65.8"	66.7"/65.9"

5TH-WHEEL TOWING

Maximum Loaded Trailer Weight Ratings (lbs.)3

Engine	Axle Ratio	GCWR	F-350 SRW 4x2	F-350 SRW 4x4	F-350 DRW 4x2	F-350 DRW 4x4	F-450 DRW 4x2	F-450 DRW 4x4	F-550 DRW 4x2	F-550 DRW 4x4
Regular Cab 6.2L 2-valve Gas	3.73	19,500 20,000	13,100	12,700	13,200	12,800	-	-	_	-
V8 FFV	4.30	23,000 23,500	16,600	16,200	16,700	16,300	_	_	_	_
6.8L 3-valve Gas V10	4.88	28,000	-	-	-	-	20,600	20,300	20,600	20,300
6.7L Diesel V8	3.73 4.10 4.30	26,500 31,000 32,000	19,200 - -	18,700 - -	23,500 24,500	- 23,100 24,100	- 23,900 26,400	23,600 26,100	- 23,900	- 23,600
	4.88	34,500 35,000 ⁴ 32,000 40,000 ⁴			- -		20,400	- - -	26,900 23,900 31,900 ⁴	26,600 23,500 31,500 ⁴
SuperCab 6.2L 2-valve Gas	3.73	19,500 20,000	12,800	12,400	12,900	- 12,500	_	-	=	_
V8 FFV	4.30	23,000 23,500	16,300	15,900	16,400	16,000	_	_	_	=
6.8L 3-valve Gas V10	4.88	28,000	-	-	-	-	20,300	20,000	20,300	20,000
6.7L Diesel V8	3.73	26,500 31,000 32,000	18,800	18,400	23,100 24,100	22,700 23,700	23,600	- 23,200	- 23,600	- 23,200
	4.30	34,500 35,000	_	-	- - -	25,700	26,100	25,700	26,600	26,200
	4.88	32,000 40,000 ⁴	-	_	=	_	-	-	23,500 31,500 ⁴	23,200 31,200 ⁴
Crew Cab 6.2L 2-valve Gas	3.73	19,500 20,000	12,600	12,200	12,700	12,300	_	-	-	=
V8 FFV	4.30	23,000 23,500	16,100	15,700	16,200	- 15,800	_	-	-	_
6.8L 3-valve Gas V10	4.88	28,000	-	-	-	-	20,200	19,900	20,200	19,900
6.7L Diesel V8	3.73	26,500 31,000	18,600	18,200	23,000	22,600	-	-	-	-
	4.10 4.30	32,000 34,500 35,000		_	24,000 - -	23,600	23,400 25,900 -	23,100 25,600 -	23,400 - 26,400	23,100 - 26,100
	4.88	32,000 40,000 ⁴	-	-	_	_	-	_	23,400 31,400 ⁴	23,100 31,100 ⁴

SRW = single rear wheel DRW = dual rear wheel

¹Ambulance Prep Package F-350 DRW: rear tire outside width is 95.2." ²When properly configured. ³F-350 DRW/F-450/F-550 weights shown are for 145.3" wheelbase Regular Cab, 167.9" wheelbase SuperCab or 179.8" wheelbase Crew Cab models. For 169.3," 191.9," 193.3," 203.8" and 205.3" wheelbase models, weights may be somewhat less (usually not more than 200 lbs., or 400 lbs. with 205.3" wheelbase). ⁴Requires High-Capacity Trailer Tow Package.

Load rating represents maximum allowable weight of people, cargo and body equipment and is reduced by the weight of optional equipment.

5th-Wheel Towing Notes: Trailer weights shown assume 400 lbs.-800 lbs. second-unit body weight. Be sure combined weight of vehicle and trailer does not exceed listed GCWR. Trailer kingpin load weight should be 15% of total loaded trailer weight. Make sure that the vehicle payload (reduced by option weight) will accommodate trailer kingpin load weight and the weight of passengers and cargo added to the towing vehicle. The addition of trailer kingpin load weight, and the weight of passengers and cargo, cannot cause vehicle weights to exceed the rear GAWR (Gross Axle Weight Rating) or GVWR (Gross Vehicle Weight Rating). These ratings can be found on the vehicle's Safety Compliance Certification Label. See your Ford Dealer for conventional trailer weights.

WHEELS/TIRES | S:Standard 0:Optional

	XI	XLT	LARIAT	
1	0	0		17" Argent-Painted Steel with Painted Center Cap (SRW)
2	S			18" Argent-Painted Steel with Painted Center Cap (SRW)
3		S		18" Cast-Aluminum with Bright Center Cap (SRW)
4			S	18" Bright-Machined Cast-Aluminum with Bright Center Cap (SRW)
5	S	S		17" Argent-Painted Steel without Center Cap (F-350 DRW)
6	0	0		17° Stainless Steel Covers, Front and Rear¹ (F-350 DRW)
7	0	0	S	17" Polished Forged-Aluminum with Bright Center Cap ² (F-350 DRW)
8	S	S		19.5" Argent-Painted Steel without Center Cap (F-450/F-550)
9	0	0		19.5" Stainless Steel Covers, Front and Rear¹ (F-450/F-550)
10		0	S	19.5" Polished Forged-Aluminum with Bright Center Cap ² (F-450/F-55

XI	XLT	LARIAT		XL	XLT	LARIAT					
0	0	7	LT245/75Rx17E BSW all-season (SRW 4x2)	S	S	S	225/70Rx19.5G BSW all-season (F-450/F-550)				
S	S	S	LT245/75Rx17E BSW all-season (F-350 DRW)	0	0	0	225/70Rx19.5G BSW traction (F-450/F-550;				
0	0		LT245/75Rx17E BSW all-terrain (SRW)		^		includes 2 all-season tires on front and 4 traction				
0	0	0	LT245/75Rx17E BSW all-terrain (F-350 DRW)				tires on rear)				
	0	0	LT245/75Rx17 OWL all-terrain (F-350 DRW)	0	0	0	225/70Rx19.5G BSW max. traction (F-450/F-550 4x4; includes 2 traction tires on front and 4 traction				
0	0		LT265/70Rx17E OWL all-terrain (SRW)				tires on rear)				
S	S	S	LT275/65Rx18E BSW all-season (SRW)								
0	0	0	LT275/70Rx18E BSW all-terrain plus (SRW 4x4)		7						
	0	0	LT275/70Rx18E OWL all-terrain (SRW 4x4)								





















¹Restrictions may apply. See your dealer for details. ²Inner rear wheels are steel.

New Vehicle Limited Warranty. We want your Ford F-Series Super Duty® Chassis Cab ownership experience to be the best it can be. Under this warranty, your new vehicle comes with 3-year/36,000-mile bumper-to-bumper coverage, 5-year/60,000-mile Powertrain Warranty coverage, 5-year/60,000-mile safety restraint coverage, and 5-year/unlimited-mile corrosion (perforation) coverage - all with no deductible. The Ford 6.7L Power Stroke® diesel engine gets 5-year/100,000-mile warranty coverage. Please ask your Ford Dealer for a copy of this limited warranty.

Roadside Assistance. Covers your vehicle for 5 years or 60,000 miles, so you have the security of knowing that help may be only a phone call away should you run out of fuel, lock yourself out of the vehicle or need towing. Your Ford Dealer can provide complete details on all of these advantages.

Ford Commercial Vehicle Center. Each of the 678 dealerships in our Commercial Vehicle Center (CVC) network is committed to providing quality commercial-oriented products and service, as well as special financing and billing arrangements, to businesses that rely on Ford products. As a CVC customer, your business vehicles receive priority service at your CVC dealership to help get your vehicle back on the road quickly.

Financial Services. Our commercial purchase plans and lines of credit offer attractive rates, negotiable terms and business-friendly options. If you prefer to lease, our CommerciaLease^{5M} programs offer a wide variety of package options to meet your needs. For additional information, please visit our website at fordcredit.com/comlend.

Ford Credit. Get the ride you want. Whether you plan to lease or finance, you'll find the choices that are right for you at Ford Credit. Ask your Ford Dealer for details or check us out at fordcredit.com.

Ford Protect™ Extended Service Plans. Whether you purchase or lease your Ford vehicle, insist on genuine Ford Protect extended service plans. Ford Protect has a variety of plans to give you peace-of-mind protection whether you want vehicle component or maintenance coverage. Plus, they are fully backed by Ford and honored at all Ford dealerships in the U.S., Canada and Mexico. When you visit your dealer, nsist on genuine Ford Protect extended service plans.

Android, Android Auto, Google, Google Maps, Waze and logos are trademarks of Google Inc. Apple, Apple CarPlay, Apple Music, iPhone and Siri are trademarks of Apple Inc., registered in the U.S. and other countries. "HD Radio" and the HD Radio logo are proprietary trademarks of iBiquity Digital Corporation. PANDORA, the PANDORA logo, and the Pandora trade dress are trademarks or registered trademarks of Pandora Media, Inc. Used with permission. Sirius, XM and all related marks and logos are trademarks of Sirius XM Radio Inc. Sony is a registered trademark of the Sony Corporation. Spotify is a registered trademark of Spotify AB, Sweden.

Comparisons based on competitive models (Class 3-5 Chassis Cabs based on Ford segmentation), publicly available information and Ford certification data at time of printing. Vehicles may be shown with optional and aftermarket equipment. Features may be offered only in combination with other options or subject to additional ordering requirements/limitations. Dimensions and capacity ratings shown may vary due to optional features and/or production variability. Information is provided on an "as is" basis and could include technical, typographical or other errors. Ford makes no warranties, representations, or guarantees of any kind, express or implied, including but not limited to, accuracy, currency, or completeness, the operation of the information, naterials, content, availability, and products. Ford reserves the right to change product specifications, pricing and equipment at any time without incurring obligations. Your Ford Dealer is the best source of the most up-to-date information on Ford vehicles. Body manufacturers are responsible for compliance certification of the completed vehicle. The Ford New Vehicle Limited Warranty and any government certification made by Ford shall cover only the vehicle as manufactured by Ford and shall not extend to any addition, modification or change of or to the vehicle by the Ford Authorized Pool Account.

ford.com/commercial-trucks/chassis-cab













As your local Ford Dealer, we go further for you. We're dedicated to serving you now and in the future. From vehicle test-drives and product demonstrations to personalized service and maintenance, we're committed to delivering a Ford ownership experience above and beyond your expectations.

