

Ford F-550® Super Duty® Chassis Cab Side-by-Side Comparison

	2024 Ford F-550 Super Duty XL Chassis Cab 60-CA 4x2 Regular Cab/SuperCab™/Crew Cab			2024 Chevrolet Silverado 5500 WT Chassis Cab 60-CA 4x2 Regular Cab/Crew Cab		2024 Ram 5500 Tradesman® Chassis Cab 60-CA 4x2 Regular Cab/Crew Cab	
Standard Engine	7.3L 2V PFI V8			6.6L Duramax® Turbo Diesel with B20 capability		6.4L HEMI® V8	
Max. Horsepower (hp @ rpm) ¹	335 @ 3,750			300 @ 2,700		370 @ 5,600	
Max. Torque (lb.-ft. @ rpm) ¹	468 @ 3,750			700 @ 1,600		429 @ 4,000	
Optional Engine	6.7L Power Stroke® V8 Turbo Diesel with B20 capability			—		6.7L Cummins® Turbo Diesel I-6	
Max. Horsepower (hp @ rpm) ¹	330 @ 2,200			—		360 @ 2,800	
Max. Torque (lb.-ft. @ rpm) ¹	950 @ 1,850			—		800 @ 1,800	
Transmission	10-speed TorqShift® automatic with SelectShift® and Selectable Drive Modes			6-speed Allison® Highway Service		6-speed AISIN® automatic	
Front Suspension	Twin-coil monobeam with shock absorbers and stabilizer bar			Taper leaf, shackle type, with shock absorbers		5-link with track bar, coil springs, stabilizer bar, solid axle	
Rear Suspension	Solid axle, leaf springs, shock absorbers and stabilizer bar			Variable-rate multi-leaf		2-stage longitudinal leaf, solid axle	
Brake System	Power 4-wheel disc brakes with Anti-Lock Brake System (ABS)			Heavy-duty hydraulic brake system with 4-channel Anti-Lock Brake System (ABS)		Power 4-wheel disc brakes with Anti-Lock Brake System (ABS)	
Steering	Electric assist hydraulic recirculating ball gear and damper			Power		Hydraulic power-assisted recirculating ball	
Airbags	6			6		2	
	Regular Cab	SuperCab	Crew Cab	Regular Cab	Crew Cab	Regular Cab	Crew Cab
Wheelbase (in.)	145.3	167.9	179.7	141.0	175.0	144.6	173.5
Cab-to-Axle (CA) (in.)	59.6	59.7	59.7	60.0	60.0	60.0	60.0
Length (in.)	230.7	253.3	265.2	224.5	258.8	236.3	265.2
Height (in.)	82.7	82.6	82.8	82.5-83.0	82.5-83.0	81.7	81.4
Track Width (Front) (in.)	74.8	74.8	74.8	n/a	n/a	77.1	77.1
Tire Outside Width (Rear) (in.)	93.9	93.9	93.9	92.7	92.7	93.2	93.2
Head Room (F/R) (in.)	40.8/—	40.8/40.3	40.8/40.4	42.8/—	42.8/40.5	39.8/—	40.9/39.8
Leg Room (F max./R) (in.)	43.9/—	43.9/33.5	43.9/43.6	45.3/—	45.3/40.9	40.9/—	40.9/40.2
Hip Room (F/R) (in.)	62.5/—	62.5/62.6	62.5/62.6	60.8/—	60.8/60.2	62.9/—	62.9/62.7
Shoulder Room (F/R) (in.)	66.7/—	66.7/66.1	66.7/65.9	64.8/—	64.8/64.3	65.9/—	65.9/65.6
Passenger Volume (cu. ft.)	64.7	116.3	131.9	n/a	n/a	62.0	125.0
Frame Rail Width (in.)	34.2	34.2	34.2	34.1	34.1	34.0	34.0
Rear Axle-to-End-of-Frame (AF) (in.)	47.2	47.2	47.2	49.0	49.0	50.8	50.8
Standard Fuel Tank Capacity (gal.)	40.0	40.0	40.0	40.0	40.0	52.0	52.0
Optional Fuel Tank Capacity (gal.)	26.5/66.5 ³	26.5/66.5 ³	26.5/66.5 ³	25.0/65.0	25.0/65.0	22.0/74.0	22.0/74.0
Standard Battery (CCA)	750	750	750	1,100	1,100	730	730
Standard Alternator (amps)	250	250	250	150	150	180	180
Standard Front Axle Rating (lbs.)	7,000	7,000	7,000	7,000	7,000	6,000	6,000
Standard Rear Axle Rating (lbs.)	13,660	13,660	13,660	11,000	11,000	13,500	13,500
Optional Rear Axle Rating (lbs.)	14,706	14,706	14,706	13,500/15,000	13,500/15,000	13,500	13,500
Standard GVWR (lbs.)	18,000	18,000	18,000	17,500	17,500	18,000	18,000
Max. GVWR (lbs.) ²	19,500	19,500	19,500	19,500	19,500	19,500	19,500
Standard GCWR (lbs.)	30,000	30,000	30,000	26,000	26,000	26,000	26,000
Max. GCWR (lbs.) ²	43,000	43,000	43,000	37,000	37,000	43,000	43,000

1. Horsepower and torque are independent attributes and may not be achieved simultaneously.
2. When properly configured. 3. Diesel engine only.

Ford F-600® Super Duty® Chassis Cab Side-by-Side Comparison

2024 Ford F-600 Super Duty XL Chassis Cab 60-CA 4x2 Regular Cab

2024 Chevrolet Silverado 6500 WT Chassis Cab 60-CA 4x2 Regular Cab

Standard Engine	7.3L 2V PFI V8	6.6L Duramax® Turbo Diesel with B20 capability
Max. Horsepower (hp @ rpm) ¹	335 @ 3,750	350 @ 2,700
Max. Torque (lb.-ft. @ rpm) ¹	468 @ 3,750	700 @ 1,600
Optional Engine	6.7L Power Stroke® V8 Turbo Diesel with B20 capability	—
Max. Horsepower (hp @ rpm) ¹	330 @ 2,200	—
Max. Torque (lb.-ft. @ rpm) ¹	950 @ 1,850	—
Transmission	10-speed TorqShift® automatic with SelectShift® and Selectable Drive Modes	6-speed Allison® Highway Service
Front Suspension	Twin-coil monobeam with shock absorbers and stabilizer bar	Taper leaf, shackle type, with shock absorbers
Rear Suspension	Solid axle, leaf springs, shock absorbers and stabilizer bar	Variable-rate multi-leaf
Brake System	Power 4-wheel disc brakes with Anti-Lock Brake System (ABS)	Heavy-duty hydraulic brake system with 4-channel Anti-Lock Brake System (ABS)
Steering	Electric assist hydraulic recirculating ball gear and damper	Power steering
Airbags	6	6
Wheelbase (in.)	145.3	141.0
Cab-to-Axle (CA) (in.)	59.6	60.0
Length (in.)	230.7	224.5
Height (in.)	83.5	82.5-83.0
Track Width (Front) (in.)	74.5	n/a
Tire Outside Width (Rear) (in.)	93.9	92.7
Head Room (F/R) (in.)	40.8/—	42.8/—
Leg Room (F max./R) (in.)	43.9/—	45.3/—
Hip Room (F/R) (in.)	62.5/—	60.8/—
Shoulder Room (F/R) (in.)	66.7/—	64.8/—
Passenger Volume (cu. ft.)	64.7	n/a
Frame Rail Width (in.)	34.2	34.1
Rear Axle-to-End-of-Frame (AF) (in.)	47.2	49.0
Standard Fuel Tank Capacity (gal.)	40.0	40.0
Optional Fuel Tank Capacity (gal.)	26.5/66.5 ³	25.0/65.0
Standard Battery (CCA)	750	1,100
Standard Alternator (amps)	250	150
Standard Front Axle Rating (lbs.)	7,500	7,000
Standard Rear Axle Rating (lbs.)	15,500	11,000
Optional Rear Axle Rating (lbs.)	15,500	13,500
Standard GVWR (lbs.)	22,000	21,500
Max. GVWR (lbs.) ²	22,000	23,500
Standard GCWR (lbs.)	31,500	26,000
Max. GCWR (lbs.) ²	43,500	37,000

1. Horsepower and torque are independent attributes and may not be achieved simultaneously.
2. When properly configured. 3. Diesel engine only.

Ford E-Series® Cutaway & Stripped Chassis Side-by-Side Comparison

	2025 Ford E-450 Cutaway	2024 Chevrolet Express 4500 Cutaway
Standard Engine	7.3L V8 Premium	6.6L V8
Max. Horsepower (hp @ rpm) ¹	325 @ 3,750	401 @ 5,200
Max. Torque (lb.-ft. @ rpm) ¹	450 @ 3,750	464 @ 4,000
Transmission	6-speed TorqShift® automatic	6-speed automatic
Front Suspension	Independent Twin-I-Beam, coil springs, shock absorbers and stabilizer bar	Independent with coil springs and stabilizer bar
Rear Suspension	Full-floating axle with dual-stage leaf springs	Hypoid drive live axle with multi-leaf springs
Brake System (F/R)	Hydraulic 4-wheel disc with Anti-Lock Brake System (ABS) and standard traction control	4-wheel disc with Anti-Lock Brake System (ABS)
Steering	Power	Power
Airbags	2	2
Wheelbase (in.)	158.0, 176.0	159.0, 177.0
Cab-to-Axle (CA) (in.)	100.0 (158" WB); 118.0 (176" WB)	100.0 (159" WB); 118.0 (177" WB)
Length (in.)	261.1	267.1 (159" WB); 285.2 (177" WB)
Height (in.)	80.5 (158" WB); 80.4 (176" WB)	83.8 (159" WB); 83.5 (177" WB)
Width (in.)	97.0 (without mirrors)	94.5
Head Room (in.)	42.0	40.9
Leg Room (in.)	42.1 (max.)	41.4
Hip Room (in.)	65.6	65.5
Shoulder Room (in.)	68.1	68.9
Frame Rail Width (in.)	42.0	42.0
Axle-to-End-of-Frame (AF) (in.)	68.5	68.4
Bumper-to-Front Axle (BA) (in.)	34.6	39.7
Fuel Tank Capacity (gal.)	55.0	32 (std.); 57 (opt.)
Max. Payload (lbs.) ^{1,2}	8,980	8,920 (159" WB); 8,870 (177" WB)
Max. Front Axle GAWR (lbs.) ³	5,000	4,600
Rear Axle GAWR (lbs.) ³	9,600	9,600
Max. GVWR (lbs.) ³	14,500	14,200
Max. GCWR (lbs.) ³	22,000	20,000
Basic Warranty Coverage ⁴	3 years or 36,000 miles ⁵	3 years/36,000 miles
Powertrain Warranty Coverage ⁴	5 years or 100,000 miles ⁵	5 years/60,000 miles
Corrosion Warranty Coverage ⁴	5 years with unlimited miles (perforation)	6 years/100,000 miles (rust-through)
24-Hour Roadside Assistance	5 years or 60,000 miles ⁵	5 years/60,000 miles

1. Horsepower, torque and payload are independent attributes and may not be achieved simultaneously. 2. When properly equipped. Max. payload varies and is based on accessories and vehicle configuration. See label on door jamb for carrying capacity of a specific vehicle. 3. When properly equipped. 4. See your dealer for limited warranty details. 5. Whichever comes first.