

2019 LINCOLN MKC

TECHNICAL SPECIFICATIONS



BODY

Construction	Unitized welded steel body
Final Assembly Location	Louisville Assembly Plant

ENGINE

Type	Turbocharged 2.0L I-4 (FWD) (AWD)	Turbocharged 2.3L I-4 (requires AWD)
Production Location	Valencia Engine Plant, Spain	Cleveland Engine Plant, USA
Configuration	Turbocharged 2.0L I-4 (FWD) (AWD)	Turbocharged 2.3L I-4 (requires AWD)
Displacement (liters)	2.0L	2.3L
Bore x Stroke	3.44 in x 3.27 in / 87.5 mm x 83.1 mm	3.44 in x 3.70 in / 87.5 mm x 94 mm
Crankshaft	Cast iron	Forged steel
Valvetrain	DOHC, four valves per cylinder, twin independent variable camshaft timing	DOHC, four valves per cylinder, twin independent variable camshaft timing
Compression Ratio	9.7:1	9.5:1
Horsepower*	245 @ 5,500	285 @ 5,500
Torque*	275 @ 3,000	305 @ 2,750
Fuel Capacity	15.7 gallons	
Fuel Delivery	High pressure, direct injection	
Fuel Economy Ratings**	FWD 2.0L I-4 AWD 2.3L I-4 AWD 2.0L I-4	20 city/27 hwy/23 combined mpg 18 city/25 hwy/20 combined mpg 19 city/25 hwy/21 combined mpg

DRIVETRAIN

Layout	Front-wheel drive	All-wheel drive
---------------	-------------------	-----------------

TRANSMISSION

	Six-speed automatic transmission with SelectShift® capability and paddle shifters	Six-speed automatic transmission with SelectShift capability and paddle shifters
--	---	--

GEAR RATIOS

First	4.584:1	
Second	2.964:1	
Third	1.912:1	
Fourth	1.446:1	
Fifth	1.000:1	
Sixth	0.746:1	
Reverse	2.943:1	
Final Drive Ratio	3.36:1 (FWD)	3.51:1 (AWD)

SUSPENSION

Front	Independent, MacPherson struts with stabilizer bar. Optional Lincoln Drive Control with adaptive suspension.
Rear	Multilink, fully independent suspension with stabilizer bar, progressive rate springs. Optional Lincoln Drive Control with adaptive suspension.

*Horsepower and torque ratings achieved with 93-octane fuel. **Actual mileage will vary.



STEERING

Type	Electronic Power-Assisted Steering	
Steering column	Manual tilt-/telescoping steering column	Power-tilt-/telescoping steering column with memory feature
Ratio	15.6:1	15.6:1
Turns, lock-to-lock	2.65	2.65
Turning circle, curb-to-curb	38 ft.	38 ft.

BRAKES

Type	Four-Wheel Anti-Lock Brakes	
Front	Vented Disc	
Rear	Solid Disc	

WHEELS AND TIRES

Wheel sizes and type Standard	18" Painted-Aluminum Wheel	18" Painted-Aluminum Wheel
Tire Size	18" Tire – P235/50R18	17" Spare Tire – T155/70D17
Wheel sizes and type Optional	19" Machined Aluminum Wheel with Premium Painted Pockets 20" Ultra-Bright-Machined Aluminum Wheels with Ebony-Painted Pockets	18" Machined Aluminum Wheel with Premium Painted Pockets 19" 5-Spoke Premium Painted-Aluminum Wheel
Tire Size for Optional wheel sizes	P235/45R19 tire P255/40R20 tire	P245/45R19 tire

DIMENSIONS (INCHES UNLESS OTHERWISE NOTED)

EXTERIOR

Wheelbase	105.9
Overall Length	179.2
Overall Height	65.2
Width with mirrors	84.1
Width with mirrors folded	76.3
Track Width	62.4/62.5

INTERIOR

Seating Capacity	5
------------------	---

HEAD ROOM

Front Seats	39.6
Rear Seats	38.7

LEG ROOM

Front Seats	42.8
Rear Seats	36.8

SHOULDER ROOM

Front Seats	56.0
Rear Seats	55.3

HIP ROOM

Front Seats	54.4
Rear Seats	52.8

WEIGHTS AND CAPACITIES

Base Curb Weight	3,811 FWD 3,969 AWD
Cargo Volume Behind Front Seats	53.1 cu. ft.
Cargo Volume Behind Rear Seats	25.2 cu. ft.
Total Passenger Volume	97.9 cu. ft.
Towing Capacity	Optional: Class II Trailer Tow Package – tow up to 3,000 lbs./2.0L and 2.3L Engines

STARTING PRICE FOR EACH TRIM LEVEL IS AS FOLLOWS*

MKC (base)	\$33,995
Select	\$36,750
Reserve	\$40,625
Black Label	\$47,200

*Includes destination and delivery charges at \$995.

Specifications are subject to change.
For more information, contact Amanda Park at 313.322.3132 or apark5@lincoln.com.



THE LINCOLN MOTOR COMPANY